## LARGE FORMAT PRINTER SURECOLOR™ SC-P10070/P20070





# A NEW ERA OF LARGE-FORMAT PRINTING BEGINS HERE.

One good printing experience is all it takes to set a new standard. The Epson SureColor<sup>™</sup> SC-P10070 and SC-P20070 professional production printers are designed to give you the best results. Epson's Advanced PrecisionCore<sup>™</sup> MicroTFP<sup>®</sup> printhead technology yields high speeds of up to 17.5 m2/h\*, with accurate dot placement for stand-out visuals. To top it all, Epson's UltraChrome<sup>™</sup> PRO nine-colour pigment ink system delivers vibrant prints with lasting durability, while a high-precision media feeding system ensures smooth, reliable operations.





SC-P10070



SC-P20070



## **ENGINEERED FOR BUSINESS**

**Rapid Speeds For Maximum Output** New PrecisionCore MicroTFP printhead utilises 8000 nozzles for class-leading print speeds of up to 17.5 m2/h\*.



### Affordable Prints with Peace of Mind

Epson's UltraChrome PRO ink with four levels of grey produces brilliant prints that last up to 200 years. Costeffective 700ml ink cartridges ensure low printing costs. Precision Media Feeding System Maximum output with Bealtime Media Adjustm

Maximum output with Realtime Media Adjustment & Feedback System, a Media Inductive Roller System and a unique Roll Media Skew Reduction System.

\*Based on 6-pass printing for high quality production, on photo media \*\*Up to 64" wide for P20070, 44" for P10070.

#### **SPECIFICATIONS** SURECOLOR™ SC-P10070/P20070



Nodel Number	SC-P10070	SC-P20070		
rinter Width	44"	64"	Dimensions & Weight	
rinting Technology		<u></u>	- SC-P10070	
rinthead	PrecisionCore ™ MicroTFP Printhead		Weight: 126kg	t
				23
rinting Method	Nozzle Verification System		-	
ozzle Configuration	Black colour ink : 4,000 nozzles (PK, MK, DGY, GY, LGY 800 nozzles each colour)			145 mm
	Colour ink : 4,000 nozzles (C, VM, Y, LC, VLM 800 nozzles each colour)			(5.7″)
Print Direction	Bi-directional printing, uni-directional printing			-
	Auto Head Alignment technology			*
rint Quality			1879 mm	🔸 🖌 760 mm
laximum Resolution	2400x1200 dpi		(73.9")	(29.9")
linimum Ink Droplet Volume	3.5pl		-	
erformance* 1	5.56		- SC-P20070 Weight: 171kg	
			weight. Tring	Î
raft Mode	600 x 600dpi, 1.9 minutes		<b>A</b>	-
lormal Mode	1200 x 1200dpi, 3.0 minutes		-	145
ine Mode	2400 x 1200dpi, 5.6 minutes			(5.
k System			-	
k Type	Epson UltraChrome ™ PRO Ink		and the second division of the second divisio	2.4
olours	Cyan, Vivid Magenta, Yellow, Photo Black, Matte Black, Da	ark Grev. Grev. Light Grev. Light Cyan.	+	1700
	Vivid Light Magenta	,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,	2415 mm	→ 760 mm (29.9″)
k Capacity			- (95.0")	(29.9")
k Capacity	700ml/110ml (Bundled)		* Figures represent print times of	nly for Epson test cample ima
rinter Software on CD-ROM			(A1 size) as shown, produced on	Premium Photo paper.
Printer Driver	WindowsXP/Vista/7/8/8.1/10 (32/64bit) or later / MacOS	X10.6.8 or later		
	Windows Server 2003 Standard/Standard *64bit, 2008 Standard/Standard *64bit /R2, 2012 or later		Man Towner	
	2003/2003 *64bit, 2008/2008R2 *64bit/2012 or later (Certification/Logo : Windows Server 2008/2008R2)		A1:588×735mr	n
aper Handling				
aper Feed Method	Friction Feed		and the second	
			- Ink Cartridge Compatibility	1
oll Dimensions	170mm		-	<i>,</i>
Paper Size & Thickness	Roll paper : 254mm (10") - 1118mm (44")	Roll paper : 254mm (10") - 1626mm (64")	700 ml Ink Cartridges	
	Cut sheet : 210mm (A4)- 1118mm (44") 0.08-1.50mm		<ul> <li>Photo Black</li> </ul>	C13T809100
Borderless	254mm(10in.), 300mm(11.8in.), 329mm(A3+/A3++),	254mm(10in.), 300mm(11.8in.), 329mm(A3+/A3++),	<ul> <li>Cyan</li> </ul>	C13T809200
	406mm(16in.), 432mm(17in./USC), 508mm(20in.),	406mm(16in.), 432mm(17in./USC), 508mm(20in.),	<ul> <li>Magenta</li> </ul>	C13T809300
	515mm(20.3in./B2), 594mm(A1), 610mm(24in./A1+),	515mm(20.3in./B2), 594mm(A1), 610mm(24in./A1+),	<ul> <li>Yellow</li> </ul>	C13T809400
	728mm(29in./B1), 841mm(A0), 914(36in./A0+),	728mm(29in./B1), 841mm(A0), 914(36in./A0+),	Light Cyan	C13T809500
	1030mm(B0), 1118mm(44in/B0+)	1030mm(B0), 1118mm(44in/B0+), 1270mm(50in.),		
			<ul> <li>Vivid Light Magenta</li> </ul>	C13T809600
		1372mm(54), 1524(60in.)	<ul> <li>Dark Grey</li> </ul>	C13T809700
oll Paper Remaining	The remaining amount is managed by the barcode print	on Roll paper.	<ul> <li>Matte Black</li> </ul>	C13T809800
Control Panel			<ul> <li>Grey</li> </ul>	C13T809900
Colour & Size	2.7" Colour LCD		<ul> <li>Light Grey</li> </ul>	C13T809000
lumber of Dots	960 x 240 pix.		Supplies & Optional Assos	
onnectivity			<ul> <li>Supplies &amp; Optional Acces</li> </ul>	
tandard	Hi-Speed USB		Auto Cutter Spare Blade	C13S210040
thernet	1000BASE-T (Recommended) / 100BASE-TX		<ul> <li>Cleaning Stick</li> </ul>	C13S090013
			<ul> <li>Maintenance Box</li> </ul>	C13T619300
ontrol Code	ESC/P raster		- Auto Take-up Reel Unit	C12C932201
lemory			Roll Adapter	C12C932231
lain	1GB	1.5GB	<ul> <li>Adobe<sup>®</sup> PostScript<sup>®</sup> 3<sup>™</sup></li> </ul>	-
oftware			Expansion Unit	C12C891131
PC Software Printer Web Function	User's Guide(EN) Network Guide(EN) , LFP RemotePanel	2, EpsonColorCalibrationUtility, EpsonNet Setup,	•	
	EpsonNet Config, EpsonNet Print (Windows only)		Hard Disk Unit	C12C848031
	'Remote Manager' HDD utility - Control of HDD functions			
oftware from Web Download	LFP Accounting Tool (Job monitoring, consumable cost t	acking), וואס סטווגע soitware (web download)	-energy w	
lectrical Specifications			ENERGY STAR	
oltage	AC100-240V 50/60Hz			
ated Current	5A		_	
ower Consumption	Operating: Approx. 95W; Sleep: Approx. 2.8W *Interface i	is 1000BASE-T; Power off (Stand-by): Less than 0.5W		
ecommended Operating			©2016 Epson India Pvt. Ltd. All	
Temperature	Operating: 10°C - 35°C; Storage: -20°C - 40°C		Reproduction in part or in whole, without the written permission from Epson, is strictly prohibited.	
Humidity	Operating: 20% - 80% (no condensation); Storage: 5% - 85% (no condensation)		- EPSON and EXCEED YOUR VISIO	N are registered
•		os a no condensationy	<ul> <li>trademarks of Seiko Epson Corp</li> </ul>	poration.
coustic Noise Level			All other product names and ot	
ound Pressure Level	Approx 50.5dB (A) Approx 51.1dB (A) less than		<ul> <li>herein are for identification pur trademarks or registered trader</li> </ul>	
ound Power Level	Approx 65.3dB (A)	Approx 67dB (A) less than	owners.	
ystem Requirement	Windows XP/Vista/7/8/8.1 (32/64bit) or later		- Epson disclaims any and all righ	
	CPU : Core 2 Duo 3.05GHz; Memory : Memory more than 1GB; HDD : Free space more than 32GB Macintosh Mac OS X10.6.8 or later		samples shown herein are simulations. The actual product design and contents may vary. Specifications are subject to change without notice and may vary between countries.	
	CPU : Core 2 Duo 3.05GHz; Memory : Memory more than 1GB; HDD : Free space more than 32GB		Please check with local Epson o	ffices for more information.
	CPUL Coro 2 Duo 2 OFCUm Moment Manager M			

EPSON INDIA PVT. LTD.

call . clear . clean

Regional Offices:

 12th Floor, The Millian Tower A, No.1,
 Ahmedabad - 2640 7176/77, Chennai - 3967 7500, Cochin - 4012 315,

 Murphy Road, Ulsoor, Bangalore - 560 005
 Oimbatore - 98942 19200, Indore - 4701 830, Kolkata - 6500 9370/77, Mumbai - 3079 8200,

 Tel: 080-30515000 Fax: 080-30515005
 New Delhi - 3312 0300/01, Pune - 3028 6000/05, Hyderabad - 6463 9640/41

CONTACT EPSON TODAY! EMAllasu@eid.epson.co.in

SOUTHAlok Singh 098405 0321 NORTHAkhtar Imam 099101 08780, Ashutosh Kumar 098153 94550, Sudhir Kumar 093898 35156AST Sourov Kumar 098746 72616/EST Milind 098209 74733

Epson Helpine: For product info or service - 1800 425 0011 Clean e-Waste to EPSON

For service - 1860 3000 1600 (9AM - 6PM) (Mon - Sat) Email: lfp@epsonindia.in

www.epson.co.in





time of printing Printed August 2016