



The Epson SureColor™ SC-S80670 is Epson's next generation, high-performance, eco-solvent signage printer. It incorporates the latest printing technologies, which include precision media feeding system and dual-performance PrecisionCore™ TFP printheads, to confidently meet the most demanding jobs. Equipped with the widest colour gamut in the new S-Series range, the SC-S80670 is set to astound with true-to-life colours in every brilliant printout.











Dual Printheads

Up to 64" wide

64"

MAX. INK CAPACITY PER COLOUR

700ML*

Environmentally Friendly







Epson UltraChrome™ GS3 ink is Greenguard Gold certified and meets the French-VOC A+ Class criteria for low chemical emissions.

Outstanding Performance

GS3

GS3INK

Print exceedingly vivid colours in outstanding quality with PrecisionCore technology and a wide colour gamut.

Steadfast Reliability

DUAL

HIGH QUALITY**

13.2

Tackle high-volume printing with ease through the newly developed precision media feeding system that allows you to print uninterrupted.

PRINT SPEEDS SQM/HR

PRODUCTION**

26.8

Optimised Design

Enjoy hassle-free operations and maintenance with automatic media alignment and setup, along with automated printhead cleaning technology.

ENGINEERED FOR BUSINESS





⁷⁰⁰ml for all colours, 600ml for white, 350ml for metallic silver.
Based on 8-pass printing for high quality and 4-pass printing for production, on banner media



MODEL NUMBER		SC-580670			
SKU No.		C11CE45402			
Printer Width		64"	64"		
Printing Tec	hnology				
Print Head		PrecisionCore™ TFP * Printhead			
Nozzle Configuration		360 x 1 x 2 nozzles each colour (x10)			
Maximum Resolution		1440 x 1440 dpi			
Minimum Ink Droplet Volume		4.2 pl			
Print Speed	· · · · · · · · · · · · · · · · · · ·				
1 Layer	Colour	Max Speed - 1 pass	Up to 95.1 m ² /h (360 x 720 dpi)		
.,.		High Speed - 2 pass (Billboard)	Up to 52.3 m ² /h (720 x 720 dpi)		
		Production 1 - 4 pass	Up to 26.8 m ² /h (720 x 720 dpi)		
		Production 2 - 6 pass	Up to 18.2 m ² /h (720 x 720 dpi)		
	Colour, Colour + White	High Quality - 8 pass	Up to 13.2 m ² /h (720 x 720 dpi)		
	coloul, colour : Trillic	Max Quality 1 - 12 pass	Up to 8.8 m ² /h (720 x 1440 dpi)		
		Max Quality 2 - 16 pass	Up to 6.8 m ² /h (720 x 1440 dpi)		
		Max Quality 3 - 30 pass	Up to 3.7 m ² /h (720 x 1440 dpi)		
		Max Quality 4 - 48 pass	Up to 2.4 m ² /h (1440 x 1440 dpi)		
	Calaria Matallia Cibran		· · · · · · · · · · · · · · · · · · ·		
	Colour + Metallic Silver	Production - 20 pass High Quality - 36 pass	Up to 4.2 m ² /h (720 x 1440 dpi) Up to 2.3 m ² /h (1440 x 1440 dpi)		
21	C-1 \ \\/\				
2 Layer	Colour + White	Speed - 18 pass	Up to 6.4 m ² /h (720 x 720 dpi)		
		Production - 32 pass	Up to 3.5 m ² /h (720 x 1440 dpi)		
		High Quality - 48 pass	Up to 2.4 m ² /h (1440 x 1440 dpi)		
	Colour + Metallic Silver	Production - 40 pass	Up to 1.9 m ² /h (720 x 1440 dpi)		
		High Quality - 72 pass	Up to 1.1 m ² /h (1440 x 1440 dpi)		
3 Layer	Colour + White	Speed - 27 pass	Up to 3.2 m ² /h (720 x 720 dpi)		
		Production - 48 pass	Up to 1.7 m ² /h (720 x 1440 dpi)		
		High Quality - 72 pass	Up to 1.1 m ² /h (1440 x 1440 dpi)		
Ink System					
Ink Type		Epson UltraChrome ™ GS3 Ink Technology with Red			
Colours		10 colours - Cyan, Magenta, Yellow, Black, Light Cyan, Light Magenta, Light Black, Orange, Red,			
		White or Metallic Silver			
Ink Capacity		700 ml (all colours except White and Metallic Silver), 600 ml (White), 350 ml (Metallic Silver)			
Paper Handling		Rear roll feed (2 " / 3 " core with max 250 mm diameter and up to 45 kg); Auto take-up reel			
Media Type		-			
Printable Area		Max printing width: 1616 mm; Side Margin: 5 mm both sides, 10 mm with media holding plates			
Media Width		300 to 1626 mm			
Media Thickness		Up to 1 mm			
Heaters		Pre- and Platen- Heater (30 to 50 °C); After-Heater (30 to 55 °C)			
Control Pan	nel	2.7" Colour LCD			
Connectivit					
Printer Inter	•	Hi-Speed USB 2.0, 100BASE-TX / 1000BA	SE-T		
Printer Land		Standard: ESC/P raster			
Printer Languages Printer Drivers		-			
Memory		512 MB main + 128 MB network			
Software		Standard: CD Installer, Communication Driver, EPSON Manuals Launcher, Operators Guides, General			
Joitware		Information, Epson Control Dashboard, EpsonNet Config, EpsonNet Setup, EpsonNet Print, Epson			
		Software Updater			
Other Features		Auto Head Alignment Technology (Media feed and Bi-directional), Auto Nozzle Check System, Mail			
		Report System, Custom Paper Backup			
Power and Operating Requirements					
Power Requirements		Input voltage AC 100 - 240 V 50/60 Hz			
Power Consumption		Operating: Approx. 745 W; Standby: Approx. 445 W w/ heater ON; Sleep: Approx. 13 W;			
		Power Off: Less than 1.8 W			
Recommended Operating					
Temperature & Humidity		15 - 35 °C; 20 - 80 % RH (non-condensing)			
Printer Dimensions					
Dimensions		2,620 x 880 x 1,338 mm (W x D x H) (storage)			
Weight		284 kg (without ink)			
Bundled Items		Substrate Support System (C12C932361), SC-S80670 Printer Starter Kit			
Warranty		Standard two years inclusive of parts and printhead			

Dimensions & Weight

SC-S80670 Weight: 284 kg (without ink)



Ink Cartridge Compatibility

 Black (700 ml) 	C13T892100
 Cyan (700 ml) 	C13T892200
 Magenta (700 ml) 	C13T892300
 Yellow (700 ml) 	C13T892400
Light Cyan (700 ml)	C13T892500
 Light Magenta (700 ml) 	C13T892600
 Light Black (700 ml) 	C13T892700
 Orange (700 ml) 	C13T892800
 Red (700 ml) 	C13T892900
 White (600 ml) 	C13T892A00
 Metallic Silver (350 ml) 	C13T892B00

Supplies & Optional Accessories

350 ml Cleaning Cartridge	C13T696000
Maintenance Parts Kit	C13S210044
Ink Cleaner	C13T699300
Cleaning Stick	C13S090013
Clean Room Wiper	C13S090016
Waste Ink Bottle	C13T724000
Additional Print Drying System	C12C932381
Media Holding Guide	C12C932411

© 2016 Epson India Pvt. Ltd. All Rights Reserved. © 2016 Epson India PVt. Ltd. All Rights Reserved. Reproduction in part or in whole, without the written permission from Epson, is strictly prohibited. EPSON and EXCEED YOUR VISION are registered trademarks of Seiko Epson Corporation. All other products names and other company names used herein are for identi fication purposes only and are the trademarks or registered trademarks of their respective owners. Epson disclaims any and all rights in those marks. Print samples shown are simulations only. Speci fications and product availability are subject to change without notice and may vary between countries. Please check with local Epson of fices for more information.

Information correct at time of printing. Printed in August 2016.

EPSON INDIA PVT. LTD. Regional Offices:

Ahmedabad - 2640 7176/77, Chennai - 3967 7500, Cochin - 4012 315, 12th Floor, The Millen Tower A, No.1,

Murphy Road, Ulsoor, Bangalore - 560 00 \$\circ\$ oimbatore - 98942 19200, Indore - 4701 830, Kolkata - 6500 9370/77, Mumbai - 3079 8200, New Delhi - 3312 0300/01, Pune - 3028 6000/05, Hyderabad - 6463 9640/41

Tel: 080-30515000 Fax: 080-30515005

CONTACT EPSON TODAY! EMAlkasu@eid.epson.co.in

SOUTHAlok Singh 098405 0321NORTHAkhtar Imam 099101 08780, Ashutosh Kumar 098153 94550, Sudhir Kumar 093898 3515EAST Sourov Kumar 098746 72616/EST Milind 098209 74733



Note: RIP Software required to print







Dealer's Stamp

