



A NEW ERA OF LARGE-FORMAT PRINTING BEGINS HERE.

One good printing experience is all it takes to set a new standard. The Epson SureColor™ SC-P10070 and SC-P20070 professional production printers are designed to give you the best results. Epson's Advanced PrecisionCore™ MicroTFP® printhead technology yields high speeds of up to 17.5 m²/h*, with accurate dot placement for stand-out visuals. To top it all, Epson's UltraChrome™ PRO nine-colour pigment ink system delivers vibrant prints with lasting durability, while a high-precision media feeding system ensures smooth, reliable operations.



SC-P10070



SC-P20070



2.64" Printhead



Up to 64" Wide**



Versatile Media Handling



Up to 1.5mm Thick



Ethernet

ENGINEERED FOR BUSINESS

Rapid Speeds For Maximum Output

New PrecisionCore MicroTFP printhead utilises 8000 nozzles for class-leading print speeds of up to 17.5 m²/h*.

Affordable Prints with Peace of Mind

Epson's UltraChrome PRO ink with four levels of grey produces brilliant prints that last up to 200 years. Cost-effective 700ml ink cartridges ensure low printing costs.

Precision Media Feeding System

Maximum output with Realtime Media Adjustment & Feedback System, a Media Inductive Roller System and a unique Roll Media Skew Reduction System.



PRECISIONCORE

EPSON ULTRACHROME
PRO INK


*Based on 6-pass printing for high quality production, on photo media.
**Up to 64" wide for P20070, 44" for P10070.

SPECIFICATIONS
SURECOLOR™ SC-P10070/P20070



Model Number	SC-P10070	SC-P20070
Printer Width	44"	64"
Printing Technology	PrecisionCore™ MicroTFP Printhead	
Printhead	PrecisionCore™ MicroTFP Printhead	
Printing Method	Nozzle Verification System	
Nozzle Configuration	Black colour ink : 4,000 nozzles (PK, MK, DGY, GY, LGY 800 nozzles each colour) Colour ink : 4,000 nozzles (C, VM, Y, LC, VLM 800 nozzles each colour)	
Print Direction	Bi-directional printing, uni-directional printing	
	Auto Head Alignment technology	
Print Quality	2400x1200 dpi	
Maximum Resolution	2400x1200 dpi	
Minimum Ink Droplet Volume	3.5pl	
Performance*1	600 x 600dpi, 1.9 minutes	
Draft Mode	600 x 600dpi, 1.9 minutes	
Normal Mode	1200 x 1200dpi, 3.0 minutes	
Fine Mode	2400 x 1200dpi, 5.6 minutes	
Ink System	Epson UltraChrome™ PRO Ink	
Ink Type	Cyan, Vivid Magenta, Yellow, Photo Black, Matte Black, Dark Grey, Grey, Light Grey, Light Cyan, Vivid Light Magenta	
Colours	Cyan, Vivid Magenta, Yellow, Photo Black, Matte Black, Dark Grey, Grey, Light Grey, Light Cyan, Vivid Light Magenta	
Ink Capacity	700ml/110ml (Bundled)	
Printer Software on CD-ROM	WindowsXP/Vista/7/8/8.1/10 (32/64bit) or later / MacOSX10.6.8 or later	
Printer Driver	Windows Server 2003 Standard/Standard *64bit, 2008 Standard/Standard *64bit /R2, 2012 or later 2003/2003 *64bit, 2008/2008R2 *64bit/2012 or later (Certification/Logo : Windows Server 2008/2008R2)	
Paper Handling	Friction Feed	
Paper Feed Method	Friction Feed	
Roll Dimensions	170mm	
Paper Size & Thickness	Roll paper : 254mm (10") - 1118mm (44") Roll paper : 254mm (10") - 1626mm (64") Cut sheet : 210mm (A4)- 1118mm (44") 0.08-1.50mm	
Borderless	254mm(10in.), 300mm(11.8in.), 329mm(A3+/A3++), 254mm(10in.), 300mm(11.8in.), 329mm(A3+/A3++), 406mm(16in.), 432mm(17in./USC), 508mm(20in.), 406mm(16in.), 432mm(17in./USC), 508mm(20in.), 515mm(20.3in./B2), 594mm(A1), 610mm(24in./A1+), 515mm(20.3in./B2), 594mm(A1), 610mm(24in./A1+), 728mm(29in./B1), 841mm(A0), 914(36in./A0+), 728mm(29in./B1), 841mm(A0), 914(36in./A0+), 1030mm(B0), 1118mm(44in/B0+), 1030mm(B0), 1118mm(44in/B0+), 1270mm(50in.), 1372mm(54), 1524(60in.)	
Roll Paper Remaining	The remaining amount is managed by the barcode print on Roll paper.	
Control Panel	2.7" Colour LCD	
Colour & Size	2.7" Colour LCD	
Number of Dots	960 x 240 pix.	
Connectivity	Hi-Speed USB	
Standard	Hi-Speed USB	
Ethernet	1000BASE-T (Recommended) / 100BASE-TX	
Control Code	ESC/P raster	
Memory	1GB 1.5GB	
Software	User's Guide(EN) Network Guide(EN) , LFP RemotePanel 2, EpsonColorCalibrationUtility, EpsonNet Setup, EpsonNet Config, EpsonNet Print (Windows only)	
PC Software	User's Guide(EN) Network Guide(EN) , LFP RemotePanel 2, EpsonColorCalibrationUtility, EpsonNet Setup, EpsonNet Config, EpsonNet Print (Windows only)	
Printer Web Function	'Remote Manager' HDD utility - Control of HDD functions	
Software from Web Download	LFP Accounting Tool (Job monitoring, consumable cost tracking), HDD Utility software (Web download)	
Electrical Specifications	AC100-240V 50/60Hz	
Voltage	AC100-240V 50/60Hz	
Rated Current	5A	
Power Consumption	Operating: Approx. 95W; Sleep: Approx. 2.8W *Interface is 1000BASE-T; Power off (Stand-by): Less than 0.5W	
Recommended Operating Temperature	Operating: 10°C - 35°C; Storage: -20°C - 40°C	
Humidity	Operating: 20% - 80% (no condensation); Storage: 5% - 85% (no condensation)	
Acoustic Noise Level	Approx 50.5dB (A) Approx 51.1dB (A) less than	
Sound Pressure Level	Approx 50.5dB (A) Approx 51.1dB (A) less than	
Sound Power Level	Approx 65.3dB (A) Approx 67dB (A) less than	
System Requirement	Windows XP/Vista/7/8/8.1 (32/64bit) or later CPU : Core 2 Duo 3.05GHz; Memory : Memory more than 1GB; HDD : Free space more than 32GB Macintosh Mac OS X10.6.8 or later CPU : Core 2 Duo 3.05GHz; Memory : Memory more than 1GB; HDD : Free space more than 32GB	

Dimensions & Weight
SC-P10070
Weight: 126kg



SC-P20070
Weight: 171kg



*1 Figures represent print times only for Epson test sample image (A1 size) as shown, produced on Premium Photo paper.



A1:588x735mm

Ink Cartridge Compatibility

700 ml Ink Cartridges

- Photo Black C13T809100
- Cyan C13T809200
- Magenta C13T809300
- Yellow C13T809400
- Light Cyan C13T809500
- Vivid Light Magenta C13T809600
- Dark Grey C13T809700
- Matte Black C13T809800
- Grey C13T809900
- Light Grey C13T809000

Supplies & Optional Accessories

- Auto Cutter Spare Blade C13S210040
- Cleaning Stick C13S090013
- Maintenance Box C13T619300
- Auto Take-up Reel Unit C12C932201
- Roll Adapter C12C932231
- Adobe® PostScript® 3™
- Expansion Unit C12C891131
- Hard Disk Unit C12C848031

©2019 Epson India Pvt. Ltd. All Rights Reserved. Reproduction in part or in whole, without the written permission from Epson, is strictly prohibited.

EPSON and EXCEED YOUR VISION are registered trademarks of Seiko Epson Corporation.

All other product names and other company names used herein are for identification purposes only and are the trademarks or registered trademarks of their respective owners.

Epson disclaims any and all rights in those marks. Print samples shown herein are simulations. The actual product design and contents may vary. Specifications are subject to change without notice and may vary between countries. Please check with local Epson offices for more information.

Information correct at time of printing
Printed June 2019

CONTACT EPSON TODAY! EMAIL: vasu@eid.epson.co.in

SOUTH Alok Singh 098405 03210, Gopala Krishna 079751 85505, Devakumar 073309 11109 **NORTH** Akhtar Imam 099101 08780, Ashutosh Kumar 098153 94550, Sudhir Kumar 093898 35156 **EAST** Sourov Kumar 098746 72616 **WEST** Milind 098209 74733, Pratik S Mhasawade 09561973709.

EPSON INDIA PVT. LTD.

12th Floor, The Millenia, Tower A, No.1, Murphy Road, Ulsoor, Bangalore - 560 008. Tel: 080-45665000 Fax: 080-45665005



Epson Helpline: For product info or service - 1800 425 0011
For service - 1800 123 001 600 (9AM - 6PM) (Mon - Sat)
Email: lfp@epsonindia.in

www.epson.co.in

