LARGE FORMAT PRINTER SURECOLOR™ SC-P6000/P7000/P8000/P9000





When quality is of paramount importance, turn to the Epson SC-P6000-9000 series. These new generation, state-of-the-art large format printers incorporate the latest colour printing technologies. With Epson's PrecisionCore™ Thin Film Piezo (TFP) printhead, they produce images accurate in detail, superior in fidelity with uncompromising image consistency. In addition, the UltraChrome™ all-pigment ink sets deliver outstanding colour accuracy and image durability in ultra-high resolution, with a wide colour gamut that achieves the most dynamic images. This range of printers seamlessly integrates with industry-leading software solutions to meet the demanding needs and the critical eye of the photo, proofing and graphic arts industry.















USB 2.0

ENGINEERED FOR BUSINESS

Advanced Printhead Technology

Highly advanced PrecisionCore printhead technology delivers incredibly consistent and accurate ink droplet placement.

Photographic Accuracy and Clarity

Epson UltraChrome inks deliver accurate colours with superb black density, achieving smooth gradations and optical clarity.

Efficient Workflow Solutions

Epson's innovative software solutions help manage printing processes, achieving affordable professional output.







The SC-P6000-9000 family of printers represents a level of technology unprecendented in Epson's history, capable of producing professional and gallery-quality photographs and artworks, as well as detailed colour reproductions for exacting proofing applications. In addition, the PrecisionCore TFP printhead with Variable Sized Droplet Technology delivers extraordinary print performance and long-lasting quality.




Advanced Printhead Technology



This new line-up of printers delivers extraordinary performance for the professional printing industry, along with unparalleled colour-matching capabilities, all these enabled by Epson's

PrecisionCore technology. Possibly the most advanced inkjet printhead technology ever developed, this revolutionary printhead is capable of producing outstanding performance and long-lasting quality with ultra-precise control of dot size, shape and placements.

To further ensure high quality results every time, the print nozzles are also capable of producing a wide variety of droplet sizes, which enables both fine detail and quick filling of larger areas—all at a single pass.



Photographic Accuracy and Clarity

UltraChrome Inks






There are many variables in the colour reproduction process generated by the Epson P-series and any one of which may affect the quality of the PANTONE colour simulation, including: type of driver or RIPI used, type of paper used, type of ink, toner or colourant used, resolution, rendering intent used, dot structures/halftones/screening, print engine and other print settings.

The SC-P6000/P8000 leverage the eight-colour UltraChrome HD ink while the SC-P7000/P9000 incorporate a reformulated Epson UltraChrome HDX 10-colour ink set. Both professional ink sets deliver outstanding colours with improved black density and higher D-Max value. The new black ink is

1.5 times denser than previous ink formulation, providing significant improvements to overall contrast ratio and optical clarity, and Microcrystal Encapsulation $^{\mathbb{T}}$ technology delivers superior gloss uniformity. Both inks are compatible with the widest range of certified proofing media in the industry, delivering superior colour consistency, proof after proof.

Higher Matte Black pigment density at media surface



The proven Epson UltraChrome pigment inks offer smooth gradation and sharp definition, by utilising a three-level black ink technology that simultaneously employs black, light black and light light black ink to produce brilliant black density and grey balance. At the media surface, the UltraChrome HDX and HD matte and photo black inks achieve a much higher pigment density, ensuring the pigments do not penetrate too deeply when printing on third-party media.



The Ultrachrome HDX ink set on the SC-P7000/P9000 achieves wider colour gamut with the newly-added violet ink, providing the ultimate proofing solution. The extreme colour gamut makes it possible to hit spot and client-specific colours accurately, capable of achieving an unparalleled 99% max certified PANTONE coverage*.

Users also have the option to use light light black instead of violet ink for high-end photographic and fine art applications. This ink configuration helps achieve superior print quality for both colour and monochrome reproductions.

"PANTONE" is the property of Pantone LLC. 99% coverage of PANTONE FORMULA GUIDE solid coated palette based on Epson Proofing Paper White Semi-matte printed with Epson printer driver at 2880x1440dpi. PANTONE coverage may vary when printed with a third-party RIP.



Epson AccuPhoto HDR Screening

Printers can see the difference the advanced ten-colour screening algorithm makes. Print results show superior colour and clarity, producing extremely fine blends and subtle photographic transitions. The most critical eye will see accurate highlight-to-shadow details with no visible photographic graininess. Regardless of the viewing light source, prints reveal a consistent colour balance. Combined with the precise dot placement accuracy of the PrecisionCore TFP printhead, overall photographic print quality shows a dramatic improvement.


Efficient Workflow Solutions

Epson Color Calibration Utility

To enable you to work more efficiently across multiple networked printers, the SC-P6000–9000 series comes with the Epson Color Calibration Utility. This measures colour density and concentration and allows you to manage your printer network from a central point which makes calibrating your printers easier and faster.

Once the base printer is set as the standard, the derivatives can calibrate their colours based on the base printer by transferring the colour chart. What's more, the calibrated data can be used for all media types and print modes and is stored directly on the printer, eliminating the hassle of exporting and importing every time you share data.

The overall benefit is a significant reduction in the amount of manual process required to run your printers.



This plug-in for Adobe Photoshop, Lightroom, and Nikon ViewNX-i includes a set of template layouts and supports ICC soft proofing, colour production, preview, custom media registration and panorama layouts. It comes with a set of colour modes as well, including advanced black and

white, for creating different finishes and moods.

It offers flexibility to print a variety of display requirements. Images can be printed individually or as a compound, borderless or with a choice of border sizes and styles. There is even an advanced gallery wrap function suitable for images to be mounted onto frames. It operates via intuitive and consistent controls including slider bars and colour wheels for precise and easy adjustments.



Superior Connectivity

The new machines come with Hi-Speed USB 2.0 and Ethernet connectivity, with support for professional Epson photographic drivers for Macintosh® and Windows®, as well as being supported by most leading third-party software RIPs and workflows.

Advanced Media Handling and Loading

To make the printing process quicker and simpler, the Epson SC-P6000–9000 printers offer:

Epson ePlaten™ Technology

Highly accurate automatic media loading and handling and fast, spindle-free roll media support for less chance of media damage

Professional Media Handling

The P-series is compatible with virtually any media type; in roll or cut sheet, up to 24 or 44 inches wide, as well as an accurate loading of cut-sheet media of up to 1.5 mm thick posterboard. All media is front-loaded via a unique straight-through media path. A printer and driver based media identification and synchronisation

system provides virtually error-free media use. Available on the SC-P9000, there is an optional Automatic Take-up Reel System allowing large print runs to go through unattended.

Epson ePlaten Media Loading Technology

For less chance of media damage and to simplify the overall roll and cut-sheet media loading process, the printers offer accurate and automatic media loading movement, skew adjustment and tracking.

Spindle-Free Roll Media Loading

Designed to work with Epson's ePlaten technology, the user-adjustable roll media adapters accept either 2 or 3-inch media cores. A simple tension lever ensures quick and secure media core loading. Additional media adapter pairs are available as accessories for efficient roll media switching.



Roll Media Length Tracking and Identification System

This system is useful for tracking partially used media rolls. It enables real-time, automatic measurement of remaining roll media length as well as auto barcode tagging of remaining roll media for faster reloading.

Intelligent High-Capacity Ink System

Pressurised ink cartridge technology ensures that ink is reliably delivered at all print speeds, while dramatically reducing the physical size of the ink cartridges. The cartridges themselves are available in sizes up to 700ml

These can be replaced on-the-fly to make sure your print run never needs to be interrupted and for even greater flexibility, the cartridges can be mixed and matched across all three sizes.



PARTNERS IN PERFECTION



Epson Signature Worthy Media

Designed in collaboration with the world's leading creative professionals, only the very highest quality papers are good enough to be called Signature Worthy. They make the perfect final step to creating a memorable image that will last for years.



Bring out true quality in your photo collection with the SureColor SC-P807. Using UltraChrome HD ink, it delivers unprecedented black density and true-to-life colour gradations and definitions.

Options





Available as an optional add-on, the ILS30 spectrophotometer (developed jointly with X-Rite) is essential to anyone who's looking for real efficiency in the proofing industry. It is capable of extreme measurement accuracy of below 0.2 dE-CMC. It simply attaches to the front of the printer, giving users the basis for an advanced colour management system.



The ILS30 comes with a built-in print dryer to accelerate the dry-down and reading process, as well as built-in temperature sensors to read the internal mechanism and the surrounding environment. Driven by the latest front-end RIP software, the Epson SpectroProofer can automate just about any colour management process.



The ILS30 is an optional colourimeter that measures exact RGB/CMYK numbers—making it perfect for proofing, while the Epson Color Calibration Utility is a standard installed software that measures colour density and concentration. The rough RGB/CMYK number is calculated by the colour density/concentration through LUT, making it suitable for colour adjustment in a printer or in multiple printers.



Internal Print Server

The printers come with an optional 320GB HDD server. It is designed to improve print queue management and boost workgroup productivity by enabling multiple jobs to be sent to the printer while processing other work.



The HDD operates like a low cost print server improving work group productivity while also helping to reduce network traffic. A web-based management utility enables the queue to be adjusted to suit priorities.



SPECIFICATIONS

SURECOLOR TM SC-P6000/P7000/P8000/P9000



Charles of Tarabase Lances		SC-P6000	SC-P8000	SC-P7000	SC-P9000
Printing Technology	Printing Method	PrecisionCore™TFP printhead, Epson Variable-Sized Droplet Technology		<u> </u>	
	Black Nozzle Configuration	360 nozzles each colour (X3)		Light Light Black ink is use: 360 nozzles each col	iour (x3)
	2 1 1 1 0 0 0 miles			Violet ink is use: 360 nozzles each colour (x2)	
	Colour Nozzle Configuration	360 nozzles each colour (X5)	Į.	Light Light Black ink is use: 360 nozzles each colo	.our (x7)
	Print Direction	Violet ink is use : 360 nozzles each colour (x8) Bi-directional printing, uni-directional printing			
	Print Direction	Bi-directional printing, uni-directional printing Auto Head Alignment Technology Auto Nozzle Check Technology			
		Auto-switching between Photo bk and Matte	∽ DK		
		Bar-code Print System			
rint Quality	Maximum Resolution	2880x1440 dpi			
IIIt Quanty	Minimum Ink Droplet Volume	3.5pl			
erformanče	Draft Mode	360 x 360dpi, 0.8 minutes			
Homanec	Normal Mode	360 x 720dpi, 1.5 minutes			
	Fine Mode	720x x720dpi, 3.3 minutes			
	Super Fine Mode	720 x 1440dpi, 8.1 minutes			
	Super Photo Mode	2880 x 1440dpi, 13.4 minutes			
ık System		Epson UltraChrome HD		Epson UltraChrome HDX	
,		Cyan, Photo Black, Matte Black, Vivid Magenta,	Yellow,Light Cyan,Vivid Light Magenta,Ligh	t Gjærk,Pirghto Black,Matte Black,Vivid Magenta	a,Yellow,Orange,Green,Light Cyan,Vivid Light N
		Light Black		Black,Light Light Black	
		<u> </u>		Cyan, Photo Black, Matte Black, Vivid Magenta	a,Yellow,Orange,Green,Light Cyan,Vivid Light N
				Black, Violet	
k Capacity	• —	700ml/350ml/150ml/ 110ml (Bundled)			
rinter Software on CD-ROM	Printer Driver	WindowsXP/Vista/7/8/8.1 (32/64bit) or later /		03 Standard/Standard *64bit, 2008 Standard/S	Standard
		*64bit /R2, 2012 or later (Certification/Logo: Windows			
aper Handling	Paper Path	Friction Feed			
-	Roll Dimensions	254mm-610mm, 2inch-core/3inch-core	254mm-1118mm, 2inch-core/ 3inch-core		254mm-1118mm, 2inch-core/ 3inch-core
		2inch-core: Max 103mm/ 3inch-core: Max 150m	n2inch-core:Max 103mm/ 3inch-core: Max 15	502inoh-core: Max: 103mm/3inch-core: Max: 150	nainch-core: Max:103mm/3inch-core: Max: 150m
	Paper Size (w) and Thickness	254mm (10") - 610mm (24"): Roll paper	254mm (10") - 1118mm (44"): Roll paper	254mm (10") - 610mm (24") : Roll paper	254mm (10") - 1118mm (44") : Roll paper
	· r ·	254mm (10") - 610mm (24"): Cut Sheet	210mm (A4) - 1118mm (44"): Cut Sheet	254mm (10") - 610mm (24"): Cut Sheet	210mm (A4) - 1118mm (44"): Cut Sheet
		0.08-1.50mm	0.08-1.50mm	0.08-1.50mm	0.08-1.50mm
	Borderless	254mm (10in.), 300mm (11.8in.),	728mm(29in.), 841mm (A0/33in.), 914mm ((3@54);nm (10in.), 300mm (11.8in.), 329mm	254mm (10in.), 300mm (11.8in.),
			1118mm (44in.) 728mm (29in.), 841mm		
		515mm (20.3in.), 594mm (23in.), 610mm (24in.)	(A0/33in.), 914mm (36in.), 1118mm (44in.)		515mm (20.3in.),594mm(23in.),610mm (24in.)
		I	f .		6iii28mm (29in.), 841mm (A0/33in.), 914mm (36ir
			<u> </u>	1118mm (44in.)	1118mm (44in.)
	Roll Paper Remaining	The remaining amount is managed by the ba	arcode print on roll paper.		
ontrol Panel	Colour & Size	2.7 inch Colour LCD			
	Number of Dots	960 x 240 pix			<u> </u>
nterface	<u>- </u>	Hi-Speed USB, 10BASE-T/100BASE-T/1000BASE-	<u>-T</u>		
ontrol Code		ESC/P raster			
Memory	Printer Main	1Gb			
nvironmental	Temperature	Operating: 10°C - 35°C			_
Characteristics		Storage: -20°C - 40°C			
	Humidity	Operating: 20 - 80% (no condensation)			
		Storage: 5 - 85% (no condensation)			
imensions/Weights	Dimension (W x D x H)	Stowed: 1,356 x 667 x 1,218 mm	Stowed: 1,864 x 667 x 1,218 mm	Stowed: 1,356 x 667 x 1,218 mm	Stowed: 1,864 x 667 x 1,218 mm
imensions/Weights		Printing: 1,356 x 903 x 1,218 mm	Printing: 1,864 x 1,318 x 1,218 mm	Printing: 1,356 x 903 x 1,218 mm	Printing: 1,864 x 1,318 x 1,218 mm
	Weight	Printing: 1,356 x 903 x 1,218 mm Approx. 101kg		Printing: 1,356 x 903 x 1,218 mm	
lectrical	Weight Voltage	Printing: 1,356 x 903 x 1,218 mm Approx. 101kg AC 100-240V 50/60Hz	Printing: 1,864 x 1,318 x 1,218 mm	Printing: 1,356 x 903 x 1,218 mm	Printing: 1,864 x 1,318 x 1,218 mm
Electrical	Weight	Printing: 1,356 x 903 x 1,218 mm Approx. 101kg	Printing: 1,864 x 1,318 x 1,218 mm	Printing: 1,356 x 903 x 1,218 mm	Printing: 1,864 x 1,318 x 1,218 mm
- Electrical	Weight Voltage	Printing: 1,356 x 903 x 1,218 mm Approx. 101kg AC 100-240V 50/60Hz 2A	Printing: 1,864 x 1,318 x 1,218 mm	Printing: 1,356 x 903 x 1,218 mm Approx. 101kg	Printing: 1,864 x 1,318 x 1,218 mm
- Electrical	Weight Voltage Rated Current	Printing: 1,356 x 903 x 1,218 mm Approx. 101kg AC 100-240V 50/60Hz 2A Operating: Approx. 65 W Ready: Approx. 19 W	Printing: 1,864 x 1,318 x 1,218 mm Approx. 135kg	Printing: 1,356 x 903 x 1,218 mm Approx. 101kg	Printing: 1,864 x 1,318 x 1,218 mm Approx. 135kg
Electrical	Weight Voltage Rated Current	Printing: 1,356 x 903 x 1,218 mm Approx. 101kg AC 100-240V 50/60Hz 2A Operating: Approx. 65 W Ready: Approx. 19 W 'Sleep: Approx. 20 W	Printing: 1,864 x 1,318 x 1,218 mm Approx. 135kg	Printing: 1,356 x 903 x 1,218 mm Approx. 101kg	Printing: 1,864 x 1,318 x 1,218 mm Approx. 135kg
Electrical	Weight Voltage Rated Current	Printing: 1,356 x 903 x 1,218 mm Approx. 101kg AC 100-240V 50/60Hz 2A Operating: Approx. 65 W Ready: Approx. 19 W	Printing: 1,864 x 1,318 x 1,218 mm Approx. 135kg	Printing: 1,356 x 903 x 1,218 mm Approx. 101kg	Printing: 1,864 x 1,318 x 1,218 mm Approx. 135kg
ilectrical	Weight Voltage Rated Current	Printing: 1,356 x 903 x 1,218 mm Approx. 101kg AC 100-240V 50/60Hz 2A Operating: Approx. 65 W Ready: Approx. 19 W 'Sleep: Approx. 20 W	Printing: 1,864 x 1,318 x 1,218 mm Approx. 135kg	Printing: 1,356 x 903 x 1,218 mm Approx. 101kg	Printing: 1,864 x 1,318 x 1,218 mm Approx. 135kg
dectrical Characteristics	Weight Voltage Rated Current	Printing: 1,356 x 903 x 1,218 mm Approx. 101kg AC 100-240V 50/60Hz 2A Operating: Approx. 65 W Ready: Approx. 19 W "Sleep: Approx. 2.0 W "Interface is 1000BASE-T"	Printing: 1,864 x 1,318 x 1,218 mm Approx. 135kg	Printing: 1,356 x 903 x 1,218 mm Approx. 101kg	Printing: 1,864 x 1,318 x 1,218 mm Approx. 135kg
dectrical Characteristics	Weight Voltage Rated Current Power Consumption	Printing: 1,356 x 903 x 1,218 mm Approx. 101kg AC 100-240V 50/60Hz 2A Operating: Approx. 65 W Ready: Approx. 19 W "Sleep: Approx. 20 W "Interface is 1000BASE-T" Power off (Stand-by): Less than 0.5W	Printing: 1,864 x 1,318 x 1,218 mm Approx. 135kg	Printing: 1,356 x 903 x 1,218 mm Approx. 101kg	Printing: 1,864 x 1,318 x 1,218 mm Approx. 135kg
Electrical Characteristics Accoustic Noise Level	Weight Voltage Rated Current Power Consumption Sound Pressure Level <db(a)> Sound Power Level <b(a)></b(a)></db(a)>	Printing: 1,356 x 903 x 1,218 mm Approx. 101kg AC 100-240V 50/60Hz 2A Operating: Approx. 65 W Ready: Approx. 19 W *Sleep: Approx. 20 W *Interface is 1000BASE-T" Power off (Stand-by): Less than 0.5 W 47dB(A) Less than 6.5B(A) Less than	Printing: 1,864 x 1,318 x 1,218 mm Approx. 135kg Operating: Approx. 75 W	Printing: 1,356 x 903 x 1,218 mm Approx. 101kg Operating: Approx. 65 W	Printing: 1,864 x 1,318 x 1,218 mm Approx. 135kg Operating: Approx. 75 W
Electrical Characteristics Accoustic Noise Level	Weight Voltage Rated Current Power Consumption Sound Pressure Level <db(a)></db(a)>	Printing: 1,356 x 903 x 1,218 mm Approx. 101kg AC 100-240V 50/60Hz 2A Operating: Approx. 65 W Ready: Approx. 19 W "Sleep: Approx. 20 W *Interface is 1000BASE-T" Power off (Stand-by): Less than 0.5W 47dB(A) Less than Printer Driver Easy-operation mode to offer in	Printing: 1,864 x 1,318 x 1,218 mm Approx. 135kg Operating: Approx. 75 W	Printing: 1,356 x 903 x 1,218 mm Approx. 101kg	Printing: 1,864 x 1,318 x 1,218 mm Approx. 135kg Operating: Approx. 75 W
Electrical Characteristics Accoustic Noise Level	Weight Voltage Rated Current Power Consumption Sound Pressure Level <db(a)> Sound Power Level <b(a)></b(a)></db(a)>	Printing: 1,356 x 903 x 1,218 mm Approx. 101kg AC 100-240V 50/60Hz 2A Operating: Approx. 65 W Ready: Approx. 19 W "Sleep: Approx. 20 W "Interface is 1000BASE-T" Power off (Stand-by): Less than 0.5W 47dB(A) Less than 6.58(A) Less than Printer Driver Easy-operation mode to offer ir User's Guide(EN) Network Guide(EN)	Printing: 1,864 x 1,318 x 1,218 mm Approx. 135kg Operating: Approx. 75 W	Printing: 1,356 x 903 x 1,218 mm Approx. 101kg Operating: Approx. 65 W	Printing: 1,864 x 1,318 x 1,218 mm Approx. 135kg Operating: Approx. 75 W
Electrical Characteristics Accoustic Noise Level	Weight Voltage Rated Current Power Consumption Sound Pressure Level <db(a)> Sound Power Level <b(a)></b(a)></db(a)>	Printing: 1,356 x 903 x 1,218 mm Approx. 101kg AC 100-240V 50/60Hz 2A Operating: Approx. 65 W Ready: Approx. 19 W "sleep: Approx. 2.0 W "Interface is 1000BASE-T" Power off (Stand-by): Less than 0.5 W 47dB(A). Less than 6.5B(A) Less than Printer Driver Easy-operation mode to offer ir User's Guide(EN) Network Guide(EN) LFP Remote Panel 2	Printing: 1,864 x 1,318 x 1,218 mm Approx. 135kg Operating: Approx. 75 W	Printing: 1,356 x 903 x 1,218 mm Approx. 101kg Operating: Approx. 65 W	Printing: 1,864 x 1,318 x 1,218 mm Approx. 135kg Operating: Approx. 75 W
Electrical Lharacterístics Accoustic Noise Level	Weight Voltage Rated Current Power Consumption Sound Pressure Level <db(a)> Sound Power Level <b(a)></b(a)></db(a)>	Printing: 1,356 x 903 x 1,218 mm Approx. 101kg AC 100-240V 50/60Hz 2A Operating: Approx. 65 W Ready: Approx. 19 W "Sleep: Approx. 20 W *Interface is 1000BASE-T" Power off (Stand-by): Less than 0.5W 47dB(A) Less than Printer Driver Easy-operation mode to offer ir User's Guide(EN) Network Guide(EN) LFP Remote Panel 2 Epson Color Calibration Utility	Printing: 1,864 x 1,318 x 1,218 mm Approx. 135kg Operating: Approx. 75 W	Printing: 1,356 x 903 x 1,218 mm Approx. 101kg Operating: Approx. 65 W	Printing: 1,864 x 1,318 x 1,218 mm Approx. 135kg Operating: Approx. 75 W
Electrical Lharacterístics Accoustic Noise Level	Weight Voltage Rated Current Power Consumption Sound Pressure Level <db(a)> Sound Power Level <b(a)></b(a)></db(a)>	Printing: 1,356 x 903 x 1,218 mm Approx. 101kg AC 100-240V 50/60Hz 2A Operating: Approx. 65 W Ready: Approx. 19 W "Sleep: Approx. 20 W "Interface is 1000BASE-T" Power off (Stand-by): Less than 0.5 W 47dB(A) Less than 6.58(A) Less than Printer Driver Easy-operation mode to offer in User's Guide(EN) Network Guide(EN) LEP Remote Panel 2 Epson Net Setup EpsonNet Setup	Printing: 1,864 x 1,318 x 1,218 mm Approx. 135kg Operating: Approx. 75 W	Printing: 1,356 x 903 x 1,218 mm Approx. 101kg Operating: Approx. 65 W	Printing: 1,864 x 1,318 x 1,218 mm Approx. 135kg Operating: Approx. 75 W
Electrical Lharacterístics Accoustic Noise Level	Weight Voltage Rated Current Power Consumption Sound Pressure Level <db(a)> Sound Power Level <b(a)></b(a)></db(a)>	Printing: 1,356 x 903 x 1,218 mm Approx. 101kg AC 100-240V 50/60Hz 2A Operating: Approx. 65 W Ready: Approx. 19 W "Sleep: Approx. 20 W *Interface is 1000BASE-T" Power off (Stand-by): Less than 0.5W 47dB(A) Less than Printer Driver Easy-operation mode to offer ir User's Guide(EN) Network Guide(EN) LFP Remote Panel 2 Epson Color Calibration Utility	Printing: 1,864 x 1,318 x 1,218 mm Approx. 135kg Operating: Approx. 75 W	Printing: 1,356 x 903 x 1,218 mm Approx. 101kg Operating: Approx. 65 W	Printing: 1,864 x 1,318 x 1,218 mm Approx. 135kg Operating: Approx. 75 W
Electrical Characteristics Accoustic Noise Level	Weight Voltage Rated Current Power Consumption Sound Pressure Level <db(a)> SOUND Power Level <b(a)> PC Software</b(a)></db(a)>	Printing: 1,356 x 903 x 1,218 mm Approx. 101kg AC 100-240V 50/60Hz 2A Operating: Approx. 65 W Ready: Approx. 19 W "Sleep: Approx. 20 W "Interface is 1000BASE-T" Power off (Stand-by): Lest than 0.5W 47dB(A) Less than Printer Driver Easy-operation mode to offer ir User's Guide(EN) Network Guide(EN) LFP Remote Panel 2 Epson Color Calibration Utility EpsonNet Setup EpsonNet Setup EpsonNet Config EpsonNet Operation (Windows only)	Printing: 1,864 x 1,318 x 1,218 mm Approx. 135kg Operating: Approx. 75 W	Printing: 1,356 x 903 x 1,218 mm Approx. 101kg Operating: Approx. 65 W	Printing: 1,864 x 1,318 x 1,218 mm Approx. 135kg Operating: Approx. 75 W
Electrical Characteristics Accoustic Noise Level	Weight Voltage Rated Current Power Consumption Sound Pressure Level <db(a)> Sound Power Level <b(a)></b(a)></db(a)>	Printing: 1,356 x 903 x 1,218 mm Approx. 101kg AC 100-240V 50/60Hz 2A Operating: Approx. 65 W Ready: Approx. 19 W "Sleep: Approx. 19 W "Sleep: Approx. 2.0 W "Interface is 1000BASE-T" Power off (Stand-by): Less than 0.5 W 47dB(A) Less than 6.5B(A) Less than 10.5B(A) Less than 10.	Printing: 1,864 x 1,318 x 1,218 mm Approx. 135kg Operating: Approx. 75 W	Printing: 1,356 x 903 x 1,218 mm Approx. 101kg Operating: Approx. 65 W	Printing: 1,864 x 1,318 x 1,218 mm Approx. 135kg Operating: Approx. 75 W
Electrical Characteristics Accoustic Noise Level Utility Software	Weight Voltage Rated Current Power Consumption Sound Pressure Level <db(a)> SOUND Power Level <b(a)> PC Software</b(a)></db(a)>	Printing: 1,356 x 903 x 1,218 mm Approx. 101kg AC 100-240V 50/60Hz 2A Operating: Approx. 65 W Ready: Approx. 19 W "Sleep: Approx. 20 W "Interface is 1000BASE-T" Power off (Stand-by): Lest than 0.5W 47dB(A) Less than Printer Driver Easy-operation mode to offer ir User's Guide(EN) Network Guide(EN) LFP Remote Panel 2 Epson Color Calibration Utility EpsonNet Setup EpsonNet Setup EpsonNet Config EpsonNet Operation (Windows only)	Printing: 1,864 x 1,318 x 1,218 mm Approx. 135kg Operating: Approx. 75 W intuitive UI, which optimum setting is autom.	Printing: 1,356 x 903 x 1,218 mm Approx. 101kg Operating: Approx. 65 W	Printing: 1,864 x 1,318 x 1,218 mm Approx. 135kg Operating: Approx. 75 W
Electrical Characteristics Accoustic Noise Level Utility Software	Weight Voltage Rated Current Power Consumption Sound Pressure Level <db(a)> Sound Power Level <b(a)> PC Software Printer Web Function</b(a)></db(a)>	Printing: 1,356 x 903 x 1,218 mm Approx. 101kg AC 100-240V 50/60Hz 2A Operating: Approx. 65 W Ready: Approx. 19 W "Sleep: Approx. 20 W *Interface is 1000BASE-T" Power off (Stand-by): Less than 0.5W 47dB(A) Less than Printer Driver Easy-operation mode to offer ir User's Guide(EN) Network Guide(EN) LFP Remote Panel 2 Epson Color Calibration Utility EpsonNet Setup EpsonNet Setup EpsonNet Config EpsonNet Operation (Windows only) "Remote Manager" HDD utility-Control of HDD functions LFP Accounting Tool (lob monitoring, consur	Printing: 1,864 x 1,318 x 1,218 mm Approx. 135kg Operating: Approx. 75 W intuitive UI, which optimum setting is autom.	Printing: 1,356 x 903 x 1,218 mm Approx. 101kg Operating: Approx. 65 W	Printing: 1,864 x 1,318 x 1,218 mm Approx. 135kg Operating: Approx. 75 W
Clectrical Characteristics Accoustic Noise Level Utility Software	Weight Voltage Rated Current Power Consumption Sound Pressure Level <db(a)> Sound Power Level <b(a)> PC Software Printer Web Function</b(a)></db(a)>	Printing: 1,356 x 903 x 1,218 mm Approx. 101kg AC 100-240V 50/60Hz 2A Operating: Approx. 65 W Ready: Approx. 19 W "Sleep: Approx. 19 W "Sleep: Approx. 2.0 W "Interface is 1000BASE-T" Power off (Stand-by): Less than 0.5 W 47dB(A) Less than 6.5B(A) Less than 16.5B(A) Less than 16.5B(A) Less than 16.5B(A) Less than 16.5B(C) Less than 16.	Printing: 1,864 x 1,318 x 1,218 mm Approx. 135kg Operating: Approx. 75 W intuitive UI, which optimum setting is autom.	Printing: 1,356 x 903 x 1,218 mm Approx. 101kg Operating: Approx. 65 W	Printing: 1,864 x 1,318 x 1,218 mm Approx. 135kg Operating: Approx. 75 W
Clectrical Characteristics Accoustic Noise Level Utility Software	Weight Voltage Rated Current Power Consumption Sound Pressure Level <db(a)> Sound Power Level <b(a)> PC Software Printer Web Function</b(a)></db(a)>	Printing: 1,356 x 903 x 1,218 mm Approx. 101kg AC 100:240 Y 50/60Hz 2A Operating: Approx. 65 W Ready: Approx. 19 W "Sleep: Approx. 20 W *Interface is 1000BASE-T" Power off (Stand-by): Less than 0.5W 47dB(A) Less than Printer Driver Easy-operation mode to offer in User's Guide(EN) Network Guide(EN) LEP Remote Panel 2 Epson Color Calibration Utility EpsonNet Setup EpsonNet Setup EpsonNet Print (Windows only) 'Remote Manage' HDD utility-Control of HDD functions LEP Accounting Tool (Job monitoring, consur Epson Print Layout (Web download)	Printing: 1,864 x 1,318 x 1,218 mm Approx. 135kg Operating: Approx. 75 W intuitive UI, which optimum setting is autom.	Printing: 1,356 x 903 x 1,218 mm Approx. 101kg Operating: Approx. 65 W	Printing: 1,864 x 1,318 x 1,218 mm Approx. 135kg Operating: Approx. 75 W
Clectrical Characteristics Accoustic Noise Level Utility Software Software from Web Download	Weight Voltage Rated Current Power Consumption Sound Pressure Level <db(a)> Sound Power Level <8(A)> PC Software Printer Web Function PC Software</db(a)>	Printing: 1,356 x 903 x 1,218 mm Approx. 101kg AC 100-240V 50/60Hz 2A Operating: Approx. 65 W Ready: Approx. 19 W "Sleep: Approx. 20 W *Interface is 1000BASE-T" Power off (Stand-by): Less than 0.5W 47dB(A) Less than Printer Driver Easy-operation mode to offer ir User's Guide(EN) Network Guide(EN) LFP Remote Panel 2 Epson Color Calibration Utility EpsonNet Setup EpsonNet Setup EpsonNet Config EpsonNet Onling EpsonNet Onling EpsonNet Onling Epson Color Calibration Utility Remote Manager' HDD utility-Control of HDD functions LFP Accounting Tool (Job monitoring, consur Epson Print Layout (Web download) LFP Print Plug-In for Office Web download) LFP Print Plug-In for Office Web download)	Printing: 1,864 x 1,318 x 1,218 mm Approx. 135kg Operating: Approx. 75 W intuitive UI, which optimum setting is autom: mable cost tracking)	Printing: 1,356 x 903 x 1,218 mm Approx. 101kg Operating: Approx. 65 W natically done simply by choosing the purpose	Printing: 1,864 x 1,318 x 1,218 mm Approx. 135kg Operating: Approx. 75 W e, such as photo, poster, CAD, document, etc
Clectrical Characteristics Accoustic Noise Level Utility Software Software from Web Download	Weight Voltage Rated Current Power Consumption Sound Pressure Level <db(a)> Sound Power Level <b(a)> PC Software Printer Web Function PC Software Automatic Take-up Reel</b(a)></db(a)>	Printing: 1,356 x 903 x 1,218 mm Approx. 101kg AC 100-240V 50/60Hz 2A Operating: Approx. 65 W Ready: Approx. 19 W "Sleep: Approx. 19 W "Sleep: Approx. 2.0 W "Interface is 1000BASE-T" Power off (Stand-by): Less than 0.5 W 47dB(A) Less than 6.5B(A) Less than 6.5B(A) Less than 10 LEP Remote Panel 2 Epson Clofo Calibration Utility EpsonNet Setup EpsonNet Config EpsonNet Ornfig EpsonNet Manager' HDD utility-Control of HDD functions LFP Accounting Tool (Job monitoring, consur Epson Print Layout (Web download) HDD Utility software (Web download) HDD Utility software (Web download) N/A	Printing: 1,864 x 1,318 x 1,218 mm Approx. 135kg Operating: Approx. 75 W intuitive UI, which optimum setting is autom.	Printing: 1,356 x 903 x 1,218 mm Approx. 101kg Operating: Approx. 65 W natically done simply by choosing the purpose	Printing: 1,864 x 1,318 x 1,218 mm Approx. 135kg Operating: Approx. 75 W
Clectrical Characteristics Accoustic Noise Level Utility Software Software from Web Download	Weight Voltage Rated Current Power Consumption Sound Pressure Level <db(a)> Sound Power Level <b(a)> PC Software Printer Web Function PC Software Automatic Take-up Reel Hard Disk Unit</b(a)></db(a)>	Printing: 1,356 x 903 x 1,218 mm Approx. 101kg AC 100:240 Y 50/60Hz 2A Operating: Approx. 65 W Ready: Approx. 19 W "Sleep: Approx. 20 W *Interface is 1000BASE-T" Power off (Stand-by): Less than 0.5W 47dB(A) Less than Printer Driver Easy-operation mode to offer in User's Guide(EN) Network Guide(EN) LEP Remote Panel 2 Epson Color Calibration Utility EpsonNet Setup EpsonNet Print (Windows only) Remote Manager HDD utility-Control of HDD functions LEP Accounting Tool (Job monitoring, consur Epson Print Layout (Web download) LEP Pint Plug-in for Office (Web download) LP Pint Plug-in for Office (Web download) N/A Capacity is 320GB C12C848031	Printing: 1,864 x 1,318 x 1,218 mm Approx. 135kg Operating: Approx. 75 W intuitive UI, which optimum setting is autom: mable cost tracking)	Printing: 1,356 x 903 x 1,218 mm Approx. 101kg Operating: Approx. 65 W natically done simply by choosing the purpose	Printing: 1,864 x 1,318 x 1,218 mm Approx. 135kg Operating: Approx. 75 W e, such as photo, poster, CAD, document, etc
Clectrical Characteristics Accoustic Noise Level Utility Software Software from Web Download	Weight Voltage Rated Current Power Consumption Sound Pressure Level <db(a)> Sound Power Level <8(A)> PC Software Printer Web Function PC Software Automatic Take-up Reel Hard Disk Unit Additional Roll Media Adapters</db(a)>	Printing: 1,356 x 903 x 1,218 mm Approx. 101kg AC 100-240V 50/60Hz 2A Operating: Approx. 65 W Ready: Approx. 19 W "Sleep: Approx. 19 W "Sleep: Approx. 20 W "Interface is 1000BASE-T" Power off (Stand-by): Less than 0.5W 47dB(A) Less than Printer Driver Easy-operation mode to offer ir User's Guide(EN) Network Guide(EN) LFP Remote Panel 2 Epson Color Calibration Utility EpsonNet Setup EpsonNet Setup EpsonNet Onling EpsonNet Print (Windows only) "Remote Manager" HDD utility-Control of HDD functions LFP Accounting Tool (Job monitoring, consur Epson Print Layout (Web download) HDD Utility software (Web download) N/A Capacity is 320GB C12C848031 C12C811241	Printing: 1,864 x 1,318 x 1,218 mm Approx. 135kg Operating: Approx. 75 W intuitive UI, which optimum setting is autom: mable cost tracking)	Printing: 1,356 x 903 x 1,218 mm Approx. 101kg Operating: Approx. 65 W natically done simply by choosing the purpose	Printing: 1,864 x 1,318 x 1,218 mm Approx. 135kg Operating: Approx. 75 W e, such as photo, poster, CAD, document, etc
Clectrical Characteristics Accoustic Noise Level Utility Software Software from Web Download	Weight Voltage Rated Current Power Consumption Sound Pressure Level <db(a)> Sound Power Level <b(a)> PC Software Printer Web Function PC Software Automatic Take-up Reel Hard Disk Unit Additional Roll Media Adapters Optional Roll Paper Belt</b(a)></db(a)>	Printing: 1,356 x 903 x 1,218 mm Approx. 101kg AC 100-240V 50/60Hz 2A Operating: Approx. 65 W Ready: Approx. 19 W "Sleep: Approx. 19 W "Sleep: Approx. 2.0 W "Interface is 1000BASE-T" Power off (Stand-by): Less than 0.5W 47dB(A) Less than 6.5B(A) Less than 6.5B(A) Less than 10.5B(A) Less than 10.5B	Printing: 1,864 x 1,318 x 1,218 mm Approx. 135kg Operating: Approx. 75 W intuitive UI, which optimum setting is autom: mable cost tracking)	Printing: 1,356 x 903 x 1,218 mm Approx. 101kg Operating: Approx. 65 W natically done simply by choosing the purpose	Printing: 1,864 x 1,318 x 1,218 mm Approx. 135kg Operating: Approx. 75 W e, such as photo, poster, CAD, document, etc
Clectrical Characteristics Accoustic Noise Level Utility Software Software from Web Download	Weight Voltage Rated Current Power Consumption Sound Pressure Level <db(a)> Sound Power Level <b(a)> PC Software Printer Web Function PC Software Automatic Take-up Reel Hard Disk Unit Additional Roll Media Adapters Optional Roll Paper Belt Auto Cutter Spare Blade</b(a)></db(a)>	Printing: 1,356 x 903 x 1,218 mm Approx. 101kg AC 100:240 Y 50/60Hz 2A Operating: Approx. 65 W Ready: Approx. 19 W "Sleep: Approx. 20 W *Interface is 1000BASE-T" Power off (Stand-by): Less than 0.5W 47dB(A) Less than Printer Driver Easy-operation mode to offer in User's Guide(EN) Network Guide(EN) LFP Remote Panel 2 Epson Color Calibration Utility EpsonNet Setup EpsonNet Setup EpsonNet Print (Windows only) Remote Manager HDD utility: Control of HDD functions LFP Accounting Tool (Job monitoring, consur Epson Print Layout (Web download) LFP Print Plug-in for Office (Web download) NA Capacity is 320GB C12C848031 C12C811241 C12C890121 C12C815331	Printing: 1,864 x 1,318 x 1,218 mm Approx. 135kg Operating: Approx. 75 W intuitive UI, which optimum setting is autom.	Printing: 1,356 x 903 x 1,218 mm Approx. 101kg Operating: Approx. 65 W natically done simply by choosing the purpose	Printing: 1,864 x 1,318 x 1,218 mm Approx. 135kg Operating: Approx. 75 W e, such as photo, poster, CAD, document, etc C12C815321
Electrical Characteristics Accoustic Noise Level Utility Software Software from Web Download	Weight Voltage Rated Current Power Consumption Sound Pressure Level <db(a)> Sound Power Level <b(a)> PC Software Printer Web Function PC Software Automatic Take-up Reel Hard Disk Unit Additional Roll Media Adapters Optional Roll Paper Belt</b(a)></db(a)>	Printing: 1,356 x 903 x 1,218 mm Approx. 101kg AC 100-240V 50/60Hz 2A Operating: Approx. 65 W Ready: Approx. 19 W "Sleep: Approx. 19 W "Sleep: Approx. 20 W "Interface is 1000BASE-T" Power off (Stand-by): Less than 0.5W 47dB(A) Less than Printer Driver Easy-operation mode to offer ir User's Guide(EN) Network Guide(EN) LFP Remote Panel 2 Epson Color Calibration Utility EpsonNet Setup EpsonNet Setup EpsonNet Setup EpsonNet Onling EpsonNet Onling EpsonNet Onling EpsonNet Onling EpsonNet Onling EpsonNet Print (Windows only) "Remote Manager" HDD utility-Control of HDD functions LFP Accounting Tool (Job monitoring, consur Epson Print Layout (Web download) HDD Utility software (Web download) N/A Capacity is 320GB C12C848031 C12C811241 C12C819311 SpectroProofer Mounter 24" (C12C890531)	Printing: 1,864 x 1,318 x 1,218 mm Approx. 135kg Operating: Approx. 75 W intuitive UI, which optimum setting is autom: mable cost tracking) C12C815321 SpectroProofer Mounter 44" (C12C890521)	Printing: 1,356 x 903 x 1,218 mm Approx. 101kg Operating: Approx. 65 W natically done simply by choosing the purpose N/A N/A	Printing: 1,864 x 1,318 x 1,218 mm Approx. 135kg Operating: Approx. 75 W e, such as photo, poster, CAD, document, etc C12C815321 SpectroProofer Mounter 44" (C12C890521)
Characteristics Accoustic Noise Level Utility Software Software from Web Download	Weight Voltage Rated Current Power Consumption Sound Pressure Level <db(a)> Sound Power Level <b(a)> PC Software Printer Web Function PC Software Automatic Take-up Reel Hard Disk Unit Additional Roll Media Adapters Optional Roll Paper Belt Auto Cutter Spare Blade SpectroProofer</b(a)></db(a)>	Printing: 1,356 x 903 x 1,218 mm Approx. 101kg AC 100-240V 50/60Hz 2A Operating: Approx. 65 W Ready: Approx. 19 W "Sleep: Approx. 19 W "Sleep: Approx. 2.0 W "Interface is 1000BASE-T" Power off (Stand-by): Less than 0.5W 47dB(A) Less than 6.5B(A) Less than 6.5B(A) Less than 10.5B(A) Less than 10.5B	Printing: 1,864 x 1,318 x 1,218 mm Approx. 135kg Operating: Approx. 75 W intuitive UI, which optimum setting is autom.	Printing: 1,356 x 903 x 1,218 mm Approx. 101kg Operating: Approx. 65 W natically done simply by choosing the purpose	Printing: 1,864 x 1,318 x 1,218 mm Approx. 135kg Operating: Approx. 75 W e, such as photo, poster, CAD, document, etc
Electrical Characteristics Accoustic Noise Level Utility Software Software from Web Download Options	Weight Voltage Rated Current Power Consumption Sound Pressure Level <db(a)> Sound Power Level <b(a)> PC Software Printer Web Function PC Software Automatic Take-up Reel Hard Disk Unit Additional Roll Media Adapters Optional Roll Paper Belt Auto Cutter Spare Blade SpectroProofer Maintenance Box</b(a)></db(a)>	Printing: 1,356 x 903 x 1,218 mm Approx. 101kg AC 100-240V 50/60Hz 2A Operating: Approx. 65 W Ready: Approx. 19 W "Sleep: Approx. 20 W *Interface is 1000BASE-T" Power off (Stand-by): Less than 0.5W 47dB(A) Less than Printer Driver Easy-operation mode to offer ir User's Guide(EN) Network Guide(EN) LFP Remote Panel 2 Epson Color Calibration Utility EpsonNet Setup EpsonNet Setup EpsonNet Print (Windows only) Remote Manager' HDD utility-Control of HDD functions LFP Accounting Tool (Job monitoring, consur Epson Print Layout (Web download) LFP Print Plug-In for Office (Web download) N/A Capacity is 320GB C12C848031 C12C81241 C12C890121 C12C913331 SpectroProofer Mounter 24" (C12C890531) +(LS30EP) C12C932021 C13T699700	Printing: 1,864 x 1,318 x 1,218 mm Approx. 135kg Operating: Approx. 75 W Intuitive UI, which optimum setting is automatically a set of the set of th	Printing: 1,356 x 903 x 1,218 mm Approx. 101kg Operating: Approx. 65 W natically done simply by choosing the purpose N/A N/A	Printing: 1,864 x 1,318 x 1,218 mm Approx. 135kg Operating: Approx. 75 W e, such as photo, poster, CAD, document, etc C12C815321 SpectroProofer Mounter 44" (C12C890521)
Electrical Characteristics Accoustic Noise Level Utility Software Software from Web Download Options	Weight Voltage Rated Current Power Consumption Sound Pressure Level <db(a)> Sound Power Level <b(a)> PC Software Printer Web Function PC Software Automatic Take-up Reel Hard Disk Unit Additional Roll Media Adapters Optional Roll Paper Belt Auto Cutter Spare Blade SpectroProofer</b(a)></db(a)>	Printing: 1,356 x 903 x 1,218 mm Approx. 101kg AC 100-240V 50/60Hz 2A Operating: Approx. 65 W Ready: Approx. 19 W "Sleep: Approx. 19 W "Sleep: Approx. 20 W "Interface is 1000BASE-T" Power off (Stand-by): Less than 0.5W 47dB(A) Less than Printer Driver Easy-operation mode to offer ir User's Guide(EN) Network Guide(EN) LFP Remote Panel 2 Epson Color Calibration Utility EpsonNet Setup EpsonNet Setup EpsonNet Setup EpsonNet Print (Windows only) "Remote Manager" HDD utility-Control of HDD functions LFP Accounting Tool (Job monitoring, consur Epson Print Layout (Web download) HDD Utility software (Web download) HDD Utility software (Web download) N/A Capacity is 320GB C12C848031 C12C811241 C12C890121 C12C815331 SpectroProofer Mounter 24" (C12C890531) +(ILS30EP) C12C932021 C13T699700 C13T834 Series UltraChrome HDX 150ml C,P	Printing: 1,864 x 1,318 x 1,218 mm Approx. 135kg Operating: Approx. 75 W Operating: Approx. 75 W intuitive UI, which optimum setting is autom; mable cost tracking C12C815321 SpectroProofer Mounter 44" (C12C890521) + (ILS30EP) C12C932021 PK, MK, VM, Y, O, G, LC, VLM, LK, LLK/V	Printing: 1,356 x 903 x 1,218 mm Approx. 101kg Operating: Approx. 65 W natically done simply by choosing the purpose N/A N/A	Printing: 1,864 x 1,318 x 1,218 mm Approx. 135kg Operating: Approx. 75 W e, such as photo, poster, CAD, document, etc C12C815321 SpectroProofer Mounter 44" (C12C890521)
Dimensions/Weights Electrical Characteristics Accoustic Noise Level Utility Software Software from Web Download Options Ink and Consumables	Weight Voltage Rated Current Power Consumption Sound Pressure Level <db(a)> Sound Power Level <b(a)> PC Software Printer Web Function PC Software Automatic Take-up Reel Hard Disk Unit Additional Roll Media Adapters Optional Roll Paper Belt Auto Cutter Spare Blade SpectroProofer Maintenance Box</b(a)></db(a)>	Printing: 1,356 x 903 x 1,218 mm Approx. 101kg Approx. 101kg AC 100:240V 50/60Hz 2A Operating: Approx. 65 W Ready: Approx. 19 W "Sleep: Approx. 20 W *Interface is 1000BASE-T" Power off (Stand-by): Less than 0.5W 47dB(A) Less than Printer Driver Easy-operation mode to offer in User's Guide(EN) Network Guide(EN) LEP Remote Panel 2 Epson Color Calibration Utility EpsonNet Setup EpsonNet Print (Windows only) 'Remote Manager' HDD utility-Control of HDD functions LEP Accounting Tool (Job monitoring, consur Epson Print Layout (Web download) LEP Print Plug-In for Office (Web download) LEP Print Plug-In for Office (Web download) LEP Print Plug-In for Office (Web download) LEP Cast 11241 C12C890121 C12C815331 SpectroProofer Mounter 24" (C12C890531) +(ILS30EP) C12C932021 C13T699700 C13T834 Series UltraChrome HDX 150ml C, P C13T824 Series UltraChrome HDX 150ml C, P	Printing: 1,864 x 1,318 x 1,218 mm Approx. 135kg Operating: Approx. 75 W Operating: Approx. 75 W Intuitive UI, which optimum setting is autom. Intuitive UI, which optimum setting is autom. C12C815321 C12C815321 SpectroProofer Mounter 44" (C12C890521) +(ILS30EP) C12C932021 PK, MK, VM, Y, O, G, LC, VLM, LK, LLK/V PK, MK, VM, Y, O, G, LC, VLM, LK, LLK/V PK, MK, VM, Y, O, G, LC, VLM, LK, LLK/V PK, MK, VM, Y, O, G, LC, VLM, LK, LLK/V	Printing: 1,356 x 903 x 1,218 mm Approx. 101kg Operating: Approx. 65 W natically done simply by choosing the purpose N/A N/A	Printing: 1,864 x 1,318 x 1,218 mm Approx. 135kg Operating: Approx. 75 W e, such as photo, poster, CAD, document, etc C12C815321 SpectroProofer Mounter 44" (C12C890521)
Electrical Characteristics Accoustic Noise Level Utility Software Software from Web Download Options	Weight Voltage Rated Current Power Consumption Sound Pressure Level <db(a)> Sound Power Level <b(a)> PC Software Printer Web Function PC Software Automatic Take-up Reel Hard Disk Unit Additional Roll Media Adapters Optional Roll Paper Belt Auto Cutter Spare Blade SpectroProofer Maintenance Box</b(a)></db(a)>	Printing: 1,356 x 903 x 1,218 mm Approx. 101kg AC 100-240V 50/60Hz 2A Operating: Approx. 65 W Ready: Approx. 19 W "Sleep: Approx. 19 W "Sleep: Approx. 20 W "Interface is 1000BASE-T" Power off (Stand-by): Less than 0.5W 47dB(A) Less than Printer Driver Easy-operation mode to offer ir User's Guide(EN) Network Guide(EN) LFP Remote Panel 2 Epson Color Calibration Utility EpsonNet Setup EpsonNet Setup EpsonNet Setup EpsonNet Print (Windows only) "Remote Manager" HDD utility-Control of HDD functions LFP Accounting Tool (Job monitoring, consur Epson Print Layout (Web download) HDD Utility software (Web download) HDD Utility software (Web download) N/A Capacity is 320GB C12C848031 C12C811241 C12C890121 C12C815331 SpectroProofer Mounter 24" (C12C890531) +(ILS30EP) C12C932021 C13T699700 C13T834 Series UltraChrome HDX 150ml C,P	Printing: 1,864 x 1,318 x 1,218 mm Approx. 135kg Operating: Approx. 75 W Operating: Approx. 75 W Intuitive UI, which optimum setting is autom. Intuitive UI, which optimum setting is autom. C12C815321 C12C815321 SpectroProofer Mounter 44" (C12C890521) +(ILS30EP) C12C932021 PK, MK, VM, Y, O, G, LC, VLM, LK, LLK/V PK, MK, VM, Y, O, G, LC, VLM, LK, LLK/V PK, MK, VM, Y, O, G, LC, VLM, LK, LLK/V PK, MK, VM, Y, O, G, LC, VLM, LK, LLK/V	Printing: 1,356 x 903 x 1,218 mm Approx. 101kg Operating: Approx. 65 W natically done simply by choosing the purpose N/A N/A	Printing: 1,864 x 1,318 x 1,218 mm Approx. 135kg Operating: Approx. 75 W e, such as photo, poster, CAD, document, etc C12C815321 SpectroProofer Mounter 44" (C12C890521)
Electrical Characteristics Accoustic Noise Level Utility Software Software from Web Download Options	Weight Voltage Rated Current Power Consumption Sound Pressure Level <db(a)> Sound Power Level <b(a)> PC Software Printer Web Function PC Software Automatic Take-up Reel Hard Disk Unit Additional Roll Media Adapters Optional Roll Paper Belt Auto Cutter Spare Blade SpectroProofer Maintenance Box</b(a)></db(a)>	Printing: 1,356 x 903 x 1,218 mm Approx. 101kg Approx. 101kg AC 100:240V 50/60Hz 2A Operating: Approx. 65 W Ready: Approx. 19 W "Sleep: Approx. 20 W *Interface is 1000BASE-T" Power off (Stand-by): Less than 0.5W 47dB(A) Less than Printer Driver Easy-operation mode to offer in User's Guide(EN) Network Guide(EN) LEP Remote Panel 2 Epson Color Calibration Utility EpsonNet Setup EpsonNet Print (Windows only) 'Remote Manager' HDD utility-Control of HDD functions LEP Accounting Tool (Job monitoring, consur Epson Print Layout (Web download) LEP Print Plug-In for Office (Web download) LEP Print Plug-In for Office (Web download) LEP Print Plug-In for Office (Web download) LEP Cast 11241 C12C890121 C12C815331 SpectroProofer Mounter 24" (C12C890531) +(ILS30EP) C12C932021 C13T699700 C13T834 Series UltraChrome HDX 150ml C, P C13T824 Series UltraChrome HDX 150ml C, P	Printing: 1,864 x 1,318 x 1,218 mm Approx. 135kg Operating: Approx. 75 W Operating: Approx. 75 W intuitive UI, which optimum setting is automatically a setting is a	Printing: 1,356 x 903 x 1,218 mm Approx. 101kg Operating: Approx. 65 W natically done simply by choosing the purpose N/A N/A	Printing: 1,864 x 1,318 x 1,218 mm Approx. 135kg Operating: Approx. 75 W e, such as photo, poster, CAD, document, etc C12C815321 SpectroProofer Mounter 44" (C12C890521)
Electrical Characteristics Accoustic Noise Level Utility Software Software from Web Download Options	Weight Voltage Rated Current Power Consumption Sound Pressure Level <db(a)> Sound Power Level <b(a)> PC Software Printer Web Function PC Software Automatic Take-up Reel Hard Disk Unit Additional Roll Media Adapters Optional Roll Paper Belt Auto Cutter Spare Blade SpectroProofer Maintenance Box</b(a)></db(a)>	Printing: 1,356 x 903 x 1,218 mm Approx. 101kg AC 100-240V 50/60Hz 2A Operating: Approx. 65 W Ready: Approx. 19 W "Sleep: Approx. 20 W *Interface is 1000BASE-T" Power off (Stand-by): Less than 0.5W 47dB(A) Less than Printer Driver Easy-operation mode to offer ir User's Guide(EN) Network Guide(EN) LFP Remote Panel 2 Epson Color Calibration Utility EpsonNet Setup EpsonNet Setup EpsonNet Form (Windows only) Remote Manager' HDD utility-Control of HDD functions LFP Accounting Tool (Job monitoring, consur Epson Print Layout (Web download) LFP Print Plug-In for Office (Web download) N/A Capacity is 320GB C12C848031 C12C811241 C12C8990121 C12C815331 SpectroProofer Mounter 24" (C12C890531) +(ILS30EP) C12C932021 C13T834 Series UltraChrome HDX 150ml C, P C13T824 Series UltraChrome HDX 150ml C, P C13T824 Series UltraChrome HDX 150ml C, P C13T804 Series UltraChrome HDX 350ml C, P C13T804 Series UltraChrome HDX 350ml C, P C13T804 Series UltraChrome HDX 350ml C, P C13T804 Series UltraChrome HDX 750ml C, P	Printing: 1,864 x 1,318 x 1,218 mm Approx. 135kg Operating: Approx. 75 W Operating: Approx. 75 W intuitive UI, which optimum setting is autom: continuitive UI, which optimum setting is autom: contin	Printing: 1,356 x 903 x 1,218 mm Approx. 101kg Operating: Approx. 65 W natically done simply by choosing the purpose N/A N/A	Printing: 1,864 x 1,318 x 1,218 mm Approx. 135kg Operating: Approx. 75 W e, such as photo, poster, CAD, document, etc C12C815321 SpectroProofer Mounter 44" (C12C890521)
Electrical Characteristics Accoustic Noise Level Utility Software Software from Web Download Options	Weight Voltage Rated Current Power Consumption Sound Pressure Level <db(a)> Sound Power Level <b(a)> PC Software Printer Web Function PC Software Automatic Take-up Reel Hard Disk Unit Additional Roll Media Adapters Optional Roll Paper Belt Auto Cutter Spare Blade SpectroProofer Maintenance Box</b(a)></db(a)>	Printing: 1,356 x 903 x 1,218 mm Approx. 101kg AC 100:240V 50/60Hz 2A Operating: Approx. 65 W Ready: Approx. 19 W "Sleep: Approx. 20 W *Interface is 1000BASE-T" Power off (Stand-by): Less than 0.5W 47dB(A) Less than Printer Driver Easy-operation mode to offer in User's Guide(EN) Network Guide(EN) LEP Remote Panel 2 Epson Color Calibration Utility EpsonNet Setup EpsonNet Print (Windows only) Remote Manager HDD utility-Control of HDD functions LEP Accounting Tool (Job monitoring, consur Epson Print Layout (Web download) LEP Print Plug-In for Office (Web download) LEP Print Plug-In for Office (Web download) LEP Print Plug-In for Office (Web download) LEP Cast 1324 C12C811241 C12C890121 C12C815331 SpectroProofer Mounter 24" (C12C890531) +(ILS30EP): C12C932021 C13T699700 C13T834 Series UltraChrome HDX 350ml C, P C13T844 Series UltraChrome HDX 150ml C, P C13T844 Series UltraChrome HDX 350ml C, P C13T844 Series UltraChrome HDX 150ml C, P C13T844 Series UltraChrome HDX 350ml C, P	Printing: 1,864 x 1,318 x 1,218 mm Approx. 135kg Operating: Approx. 75 W Operating: Approx. 75 W intuitive Ui, which optimum setting is autom. C12C815321 SpectroProofer Mounter 44" (C12C890521) + (ILS30EP) C12C932021 + (ILS30EP) C12C92021 + (ILS30EP) C12C92021 + (ILS30EP) C12C92021 + (ILS30EP) C12C92021 +	Printing: 1,356 x 903 x 1,218 mm Approx. 101kg Operating: Approx. 65 W natically done simply by choosing the purpose N/A N/A	Printing: 1,864 x 1,318 x 1,218 mm Approx. 135kg Operating: Approx. 75 W e, such as photo, poster, CAD, document, etc C12C815321 SpectroProofer Mounter 44" (C12C890521)
Electrical Characteristics Accoustic Noise Level Utility Software Software from Web Download Options Ink and Consumables	Weight Voltage Rated Current Power Consumption Sound Pressure Level <db(a)> Sound Power Level <b(a)> PC Software Printer Web Function PC Software Automatic Take-up Reel Hard Disk Unit Additional Roll Media Adapters Optional Roll Paper Belt Auto Cutter Spare Blade SpectroProofer Maintenance Box Inks</b(a)></db(a)>	Printing: 1,356 x 903 x 1,218 mm Approx. 101kg AC 100-240V 50/60Hz 2A Operating: Approx. 65 W Ready: Approx. 19 W "Sleep: Approx. 20 W *Interface is 1000BASE-T" Power off (Stand-by): Less than 0.5W 47dB(A) Less than Printer Driver Easy-operation mode to offer ir User's Guide(EN) Network Guide(EN) LFP Remote Panel 2 Epson Color Calibration Utility EpsonNet Setup EpsonNet Setup EpsonNet Ornfig EpsonNet Ornfig EpsonNet Ornfig EpsonNet Ornfig EpsonNet Ornfig EpsonNet Ornfig Consumer Ornfig EpsonNet Ornfig Eps	Printing: 1,864 x 1,318 x 1,218 mm Approx. 135kg Operating: Approx. 75 W Operating: Approx. 75 W intuitive UI, which optimum setting is autom: operating: Approx. 75 W operating: Approx. 75	Printing: 1,356 x 903 x 1,218 mm Approx. 101kg Operating: Approx. 65 W natically done simply by choosing the purpose N/A N/A SpectroProofer Mounter 24" (C12C890531) +(ILS30EP) C12C932021	Printing: 1,864 x 1,318 x 1,218 mm Approx. 135kg Operating: Approx. 75 W e, such as photo, poster, CAD, document, etc C12C815321 SpectroProofer Mounter 44" (C12C890521) +(ILS30EP) C12C932021
Electrical Characteristics Accoustic Noise Level Utility Software Software from Web Download Options Ink and Consumables	Weight Voltage Rated Current Power Consumption Sound Pressure Level <db(a)> Sound Power Level <b(a)> PC Software Printer Web Function PC Software Automatic Take-up Reel Hard Disk Unit Additional Roll Media Adapters Optional Roll Paper Belt Auto Cutter Spare Blade SpectroProofer Maintenance Box</b(a)></db(a)>	Printing: 1,356 x 903 x 1,218 mm Approx. 101kg AC 100-240V 50/60Hz 2A Operating: Approx. 65 W Ready: Approx. 19 W "Sleep: Approx. 19 W "Sleep: Approx. 20 W "Interface is 1000BASE-T" Power off (Stand-by): Less than 0.5W 47dB(A) Less than Printer Driver Easy-operation mode to offer ir User's Guide(EN) Network Guide(EN) LFP Remote Panel 2 Epson Color Calibration Utility EpsonNet Setup EpsonNet Setup EpsonNet Setup EpsonNet Print (Windows only) "Remote Manager" HDD utility-Control of HDD functions LFP Accounting Tool (Job monitoring, consur Epson Print Layout (Web download) HDD Utility software (Web download) HDD Utility software (Web download) N/A Capacity is 320GB C12C848031 C12C811241 C12C890121 C13T699700 C13T834 Series UltraChrome HDX 150ml C, P C13T824 Series UltraChrome HDX 350ml C, P C13T824 Series UltraChrome HD 750ml C, P C13T824 Series Ul	Printing: 1,864 x 1,318 x 1,218 mm Approx. 135kg Operating: Approx. 75 W intuitive UI, which optimum setting is autom: mable cost tracking) C12C815321 SpectroProofer Mounter 44" (C12C890521) +(ILS30EP) C12C932021 PK, MK, VM, Y, O, G, LC, VLM, LK, LLKV PK, MK, VM, Y, O, G, LC, VLM, LK, LLKV PK, MK, VM, Y, LC, VLM, LK, LLKV PK, MK, VM, Y, LC, VLM, LK, LLK CMK, VM, Y, LC, VLM, LK, LLK CMK, VM, Y, LC, VLM, LK, LLK CMK, VM, Y, LC, VLM, LK, LLK CPU: Core 2 Duo 3.05GHz, Memory: Memory	Printing: 1,356 x 903 x 1,218 mm Approx. 101kg Operating: Approx. 65 W natically done simply by choosing the purpose N/A N/A SpectroProofer Mounter 24" (C12C890531) + (ILS30EP) C12C932021	Printing: 1,864 x 1,318 x 1,218 mm Approx. 135kg Operating: Approx. 75 W e, such as photo, poster, CAD, document, etc C12C815321 SpectroProofer Mounter 44" (C12C890521) +(ILS30EP) C12C932021
Clectrical Characteristics Accoustic Noise Level Utility Software Software from Web Download Options Ink and Consumables	Weight Voltage Rated Current Power Consumption Sound Pressure Level <db(a)> Sound Power Level <b(a)> PC Software Printer Web Function PC Software Automatic Take-up Reel Hard Disk Unit Additional Roll Media Adapters Optional Roll Paper Belt Auto Cutter Spare Blade SpectroProofer Maintenance Box Inks System Requirement</b(a)></db(a)>	Printing: 1,356 x 903 x 1,218 mm Approx. 101kg APProx. 101kg AC 100:240 Y 50/60Hz 2A Operating: Approx. 65 W Ready: Approx. 19 W "Sleep: Approx. 20 W *Interface is 1000BASE-T" Power off (Stand-by): Less than 0.5W 47dB(A) Less than Printer Driver Easy-operation mode to offer in User's Guide(EN) Network Guide(EN) LEP Remote Panel 2 Epson Color Calibration Utility EpsonNet Setup EpsonNet Print (Windows only) Remote Manager HDD utility-Control of HDD functions LEP Accounting Tool (Job monitoring, consur Epson Print Layout (Web download) HDD Utility Software (Web download) LEP Print Plug-In for Office (Web download) LEP C12639012 C12681321 C12681331 SpectroProofer Mounter 24" (C12C890531) +(ILS30EP) C12C932021 C13T699700 C13T834 Series Ultrachrome HDX 350ml C, PC C13T844 Series Ultrachrome HDX 350ml C, PC C13T844 Series Ultrachrome HD 350ml C, PC C13T845 Se	Printing: 1,864 x 1,318 x 1,218 mm Approx. 135kg Operating: Approx. 75 W intuitive UI, which optimum setting is autom: mable cost tracking) C12C815321 SpectroProofer Mounter 44" (C12C890521) +(ILS30EP) C12C932021 PK, MK, VM, Y, O, G, LC, VLM, LK, LLKV PK, MK, VM, Y, O, G, LC, VLM, LK, LLKV PK, MK, VM, Y, LC, VLM, LK, LLKV PK, MK, VM, Y, LC, VLM, LK, LLK CMK, VM, Y, LC, VLM, LK, LLK CMK, VM, Y, LC, VLM, LK, LLK CMK, VM, Y, LC, VLM, LK, LLK CPU: Core 2 Duo 3.05GHz, Memory: Memory	Printing: 1,356 x 903 x 1,218 mm Approx. 101kg Operating: Approx. 65 W natically done simply by choosing the purpose N/A N/A SpectroProofer Mounter 24" (C12C890531) + (ILS30EP) C12C932021	Printing: 1,864 x 1,318 x 1,218 mm Approx. 135kg Operating: Approx. 75 W e, such as photo, poster, CAD, document, etc C12C815321 SpectroProofer Mounter 44" (C12C890521) +(ILS30EP) C12C932021
Electrical Characteristics Accoustic Noise Level Utility Software Software from Web Download Diptions	Weight Voltage Rated Current Power Consumption Sound Pressure Level <db(a)> Sound Power Level <b(a)> PC Software Printer Web Function PC Software Automatic Take-up Reel Hard Disk Unit Additional Roll Media Adapters Optional Roll Paper Belt Auto Cutter Spare Blade SpectroProofer Maintenance Box Inks</b(a)></db(a)>	Printing: 1,356 x 903 x 1,218 mm Approx. 101kg AC 100-240V 50/60Hz 2A Operating: Approx. 65 W Ready: Approx. 19 W "Sleep: Approx. 19 W "Sleep: Approx. 20 W "Interface is 1000BASE-T" Power off (Stand-by): Less than 0.5W 47dB(A) Less than Printer Driver Easy-operation mode to offer ir User's Guide(EN) Network Guide(EN) LFP Remote Panel 2 Epson Color Calibration Utility EpsonNet Setup EpsonNet Setup EpsonNet Setup EpsonNet Print (Windows only) "Remote Manager" HDD utility-Control of HDD functions LFP Accounting Tool (Job monitoring, consur Epson Print Layout (Web download) HDD Utility software (Web download) HDD Utility software (Web download) N/A Capacity is 320GB C12C848031 C12C811241 C12C890121 C13T699700 C13T834 Series UltraChrome HDX 150ml C, P C13T824 Series UltraChrome HDX 350ml C, P C13T824 Series UltraChrome HD 750ml C, P C13T824 Series Ul	Printing: 1,864 x 1,318 x 1,218 mm Approx. 135kg Operating: Approx. 75 W intuitive UI, which optimum setting is autom: mable cost tracking) C12C815321 SpectroProofer Mounter 44" (C12C890521) +(ILS30EP) C12C932021 PK, MK, VM, Y, O, G, LC, VLM, LK, LLKV PK, MK, VM, Y, O, G, LC, VLM, LK, LLKV PK, MK, VM, Y, LC, VLM, LK, LLKV PK, MK, VM, Y, LC, VLM, LK, LLK CMK, VM, Y, LC, VLM, LK, LLK CMK, VM, Y, LC, VLM, LK, LLK CMK, VM, Y, LC, VLM, LK, LLK CPU: Core 2 Duo 3.05GHz, Memory: Memory	Printing: 1,356 x 903 x 1,218 mm Approx. 101kg Operating: Approx. 65 W natically done simply by choosing the purpose N/A N/A SpectroProofer Mounter 24" (C12C890531) + (ILS30EP) C12C932021	Printing: 1,864 x 1,318 x 1,218 mm Approx. 135kg Operating: Approx. 75 W e, such as photo, poster, CAD, document, etc C12C815321 SpectroProofer Mounter 44" (C12C890521) +(ILS30EP) C12C932021

^{*1} Figures represent print times only for the Epson test sample image as shown, produced on Plain (draft – fine modes) and Premium Photo paper (super fine & super photo modes). Print speeds are engine only with total throughput time dependant on workflow configuration, paper type, software, file format / size, print resolution, ink coverage, networking, and other factors. You servine end to choose to configure the machine with either light light black or violet. Once this once has been made, it is final and cannot be undone or switched at a later time. 99% pantone coverage requires configuration with violet ink. Configured with light black provides 98% pantone coverage.



© 2015 Epson Singapore Pte Ltd. All Rights Reserved. Reproduction in part or in whole, without the written permission from Epson, is strictly prohibited. EPSON and EXCEED YOUR VISION are registered trademarks of Seiko Epson Corporation. All other product names and other company names used herein are for identification purposes only and are the trademarks or registered trademarks of their respective owners. Epson disclaims any and all rights in those marks. Print samples shown are simulations only. Specifications and product availability are subject to change without notice and may vary between countries. Please check with local Epson offices for more information.

