



**LARGER-THAN-LIFE
PHOTO PRINTS
THAT COME ALIVE.**

Impeccable Photo Quality, Unparalleled Colour Accuracy.

Add a touch of extraordinary performance to your photo printing with the Epson SureColor™ SC-P7530 (61 cm (24")) and SC-P9530 (112 cm (44")) large format photo printers. Epson's UltraChrome™ PRO12 ink is perfectly paired with the revolutionary PrecisionCore™ MicroTFP® printhead for high-quality prints at outstanding speeds. Expect nothing short of brilliance in every print.



SC-P7530



SC-P9530

Outstanding Colour Quality

Wide colour gamut with UltraChrome™ PRO12 ink and increased black density with Black Enhance Overcoat.

Exceptional Productivity

With dedicated Matte Black and Photo Black ink channels, print jobs can be continuous.

Trusted Reliability

The printers are designed to be dust-proof with an easy access hatch for printhead cleaning to minimise downtime.

SPECIFICATIONS

SURECOLOR™ SC-P7530/P9530



MODEL NUMBER	SC-P7530	SC-P9530
Printer Width	61 cm (24")	112 cm (44")
Printing Technology	PrecisionCore™ Inkjet Technology, Variable-sized Droplet Technology	
Printing Method	MicroTFP™ Printhead	
Printhead	9600 nozzles (800 nozzles x 12 channels x 1 head)	
Nozzle Configuration	2400 x 1200 dpi	
Maximum Resolution	3.5 pl	
Minimum Ink Droplet Volume	97 sec (Level 1) 122 sec (Default) Premium Glossy	
Print Speed	219 sec (Level 1) 285 sec (Default) Premium Glossy	Photo Paper 170 g/m ² B0 size / ISO Blike
Ink System	UltraChrome™ PRO12 Pigment Ink	
Ink Type	Cyan, Vivid Magenta, Yellow, Light Cyan, Vivid Light Magenta, Orange, Green, Violet, Photo Black,	
Colours	Matte Black, Gray, Light Gray	
Ink Capacity	700 mL	
Paper Handling	Friction Feed	
Paper Path	2" roll core media: Max. 103 mm/6 kg, 3" roll core media: Max. 150 mm/10Kg	
Maximum Roll Diameter / Weight	Roll Paper: 254 mm to 620 mm, Cutsheet: 210 mm to 620 mm	Roll Paper: 254 mm to 1118 mm, Cutsheet: 210 mm to 1118 mm
Paper Width (Roll)	Roll : 0.08 mm to 0.5 mm, Cutsheet : 0.08 mm to 1.5 mm	
Paper Thickness	10.9 cm (4.3") touch screen	
Control Panel	10.9 cm (4.3") Optical Touch Colour LCD	
Connectivity	Super-Speed USB, 100BASE-TX /1000BASE-T	
Printer Interface	USB Interface (Hi-Speed USB/USB), 1000BASE-T/100BASE-TX	
Printer Language	ESC/P raster	
Memory	2 GB	
Power and Operating Requirements	AC 100 to 240 V, 50/60 Hz	
Power Requirements	3.4 - 1.6 A	
Rated Current	Operating: Approx. 85 W	Operating: Approx. 110 W
	Ready: Approx. 32 W	Ready: Approx. 32 W
	Sleep: Approx. 3.4 W	Sleep: Approx. 3.4 W
Power Consumption	Power Off (Standby): Approx. 0.3 W	Power Off (Standby): Approx. 0.3 W
Temperature	Operating: 10°C to 35°C, Storage / Packing: -20°C to 60°C, Unpacking: -20°C to 40°C	
Humidity	Operating: 20 - 80% (no condensation), Storage: 5 - 85% (no condensation)	
Acoustic Noise Level	Operating: Approx. 49.5 dB(A), Sleep: Approx. 31.5 dB(A)	
Sound Pressure Level (db(A))	Operating: Approx. 7.5 B(A)	
Sound Power Level (B(A))		
Utility Software	Windows Install Navi - Printer driver - EpsonNet Setup - EpsonNet Print - EpsonNet Config SE - Epson Software Updater - EPSON manuals - Manual Launcher - Epson Control Dashboard	
Utility Software (Bundled in CD)	Mac Setup Navi - EpsonNet Config SE - Epson Software Updater	
Utility Software (Web Delivery)	Windows Install Navi, Web Installer, Firmware Updater, PS Driver, HDI Driver, XPS Driver, Epson Media Installer, EpsonNet Setup Manager, Epson Device Admin, Epson Edge Dashboard, Epson Edge Print, Epson Print Layout, LFP Accounting Tool, Adobe ICC Profiles, Mac Web Installer, Install Navi - Printer driver - EpsonNet Config - Epson Software Updater - Uninstaller - Epson Manuals, Epson Media Installer, Firmware Updater, Linux, Printer driver	
Printer Dimensions	Storage Dimensions (W x H x D) 1,401 mm x 1,218 mm x 667 mm 1,909 mm x 1,218 mm x 667 mm	
	Printing Dimensions (W x H x D) 1,401 mm x 1,218 mm x 2,211 mm 1,909 mm x 1,218 mm x 2,211 mm	
Weight	121.7 kg	153.8 kg
What's in the box	Printer, Printer Stand, Initial Ink Cartridge, AC Power Cable, Setup Guide, Software CD-ROM, Maintenance Box	
Options	SpectroProofer, SpectroPhotoMeter, ILS30EP, Auto Take Up Reel Unit, Hard Disk Unit, Adobe PostScript 3 Expansion Unit, Roll Media Adapter	
Consumables	Ink Cartridge, Maintenance Box, Auto Cutter Spare Blade, Borderless Replacement Pad Kit	

SC-P7530

Dimensions & Weight

Weight: 121.7 kg



SC-P9530

Dimensions & Weight

Weight: 153.8 kg



Supplies & Optional Accessories

SC-P7530	C11CH12402
SC-P9530	C11CH13402
SC-P7530/9530 PK IC (700 mL)	C13T44N100
SC-P7530/9530 CY IC (700 mL)	C13T44N200
SC-P7530/9530 VM IC (700 mL)	C13T44N300
SC-P7530/9530 YL IC (700 mL)	C13T44N400
SC-P7530/9530 LC IC (700 mL)	C13T44N500
SC-P7530/9530 LI IC (700 mL)	C13T44N600
SC-P7530/9530 LB IC (700 mL)	C13T44N700
SC-P7530/9530 MK IC (700 mL)	C13T44N800
SC-P7530/9530 LI IC (700 mL)	C13T44N900
SC-P7530/9530 OR IC (700 mL)	C13T44NA00
SC-P7530/9530 GR IC (700 mL)	C13T44NB00
SC-P7530/9530 VI IC (700 mL)	C13T44ND00

© 2022 Epson India Pvt Ltd. All Rights Reserved. Reproduction in part or in whole, without the written permission from Epson, is strictly prohibited. EPSON and EXCEED YOUR VISION are registered trademarks of Seiko Epson Corporation. All other product names and other company names used herein are for identification purposes only and are the trademarks or registered trademarks of their respective owners. Epson disclaims any and all rights in those marks. Print samples shown are simulations only. Specifications and product availability are subject to change without notice and may vary between countries. Please check with local Epson offices for more information.

Information correct as of July 2022

EPSON INDIA PVT. LTD.

12th Floor, The Millenia, Tower A, No.1, Murphy Road, Ulsoor, Bangalore - 560 008. Tel: 080-4566 5000 | Fax: 080-4566 5005

CONTACT EPSON TODAY I EMAIL: vasu@eid.epson.co.in

NORTH Delhi NCR, Haryana, Uttarakhand: Akhtar Imam 99101 08780 **Punjab, Chandigarh, Jammu & Kashmir:** Ashutosh Kumar 98153 94550

Uttar Pradesh, Bihar: Sudhir Kumar 93898 35156 **Madhya Pradesh, Rajasthan:** Mumandra Singh 73034 19414 | **EAST West Bengal,**

North East: Surov Kumar 98746 72616 **Orissa, Jharkhand:** Subhadeep Guha 90731 57783 | **WEST Mumbai, Pune, Goa, Chhattisgarh,**

Nagpur: Pratik S Mhaswade 95619 73709 **Gujarat:** Hitesh Wadekar 97250 18025 | **SOUTH Tamil Nadu, Kerala:** Alok Singh 98405 03210

Karnataka: Gopala Krishna 79751 85505 **Andhra Pradesh, Telangana:** Devakumar 73309 11109

Dealer's Stamp



Epson Helpline: For product info or service - 1800 425 0011
For service - 1800 123 001 600 or 1860 3000 1600 (9 am - 6 pm) (Mon- Sat)
Email: lp@epson-india.in

www.epson.co.in